



SASSO 100 round

semi-recessed


EN Cylindrical semi-recessed spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; luminaire housing can be attached to mounting plate without tools by interlock; light inset rotatable and tiltable; symmetric radiation characteristic - precise due to high quality lens system; with different beam angles; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable

IT Faretto cilindrico in alluminio con montaggio a semincasso; superficie dell'insero verniciata; superficie housing verniciata a polv.; corpo illuminante montabile ad appoggio senza attrezzi su piastra di montaggio tramite blocco di sicurezza; inserto luce girevole e orientabile; emissione simmetrica - precisa grazie all'ottica a lente di alta qualità; con diversi angoli di emissione; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica; convertitore esterno da inserire nel soffitto, cablaggio passante adatto

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
tunable white 1800 K - 4000 K,
tunable white 2700 K - 6500 K
CRI ≥ 90 , CRI ≥ 92 / 2 SDCM, 3
SDCM
UGR ≤ 10 , UGR ≤ 13 , UGR ≤ 16 ,
UGR ≤ 19
fino a 127 lm/W
L80 / 50000 h, L85 / 50000 h,
L90 / 50000 h
DALI-2, non DIM
front IP20

Types



Colore



Colore interno



Distribuzione della luce



wallwasher and
wallwasher
floor inset



glare control
(UGR ≤ 16)





easy mounting
no visible
screws



Colour Warm
Dimming 1800
- 3000 K
(optional)



CRI ≥ 95 2
SDCM
(optional)



SASSO 100 round adjustable semi-recessed



SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
15.2 W, 450 mA	2700 K	1740 lm	115 lm/W	0 4 8 - 3 4 0 1 9 1 <input checked="" type="checkbox"/> S
	3000 K	1800 lm	118 lm/W	0 4 8 - 3 4 0 1 0 1 <input checked="" type="checkbox"/> S
	3500 K	1840 lm	121 lm/W	0 4 8 - 3 4 0 1 2 1 <input checked="" type="checkbox"/> S
	4000 K	1880 lm	123 lm/W	0 4 8 - 3 4 0 1 1 1 <input checked="" type="checkbox"/> S

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to inner colour traffic white.

MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
15.2 W, 450 mA	2700 K	1750 lm	115 lm/W	0 4 8 - 3 4 0 1 9 1 <input checked="" type="checkbox"/> M
	3000 K	1800 lm	118 lm/W	0 4 8 - 3 4 0 1 0 1 <input checked="" type="checkbox"/> M
	3500 K	1840 lm	121 lm/W	0 4 8 - 3 4 0 1 2 1 <input checked="" type="checkbox"/> M
	4000 K	1890 lm	124 lm/W	0 4 8 - 3 4 0 1 1 1 <input checked="" type="checkbox"/> M

The data values for the luminaire luminous flux may differ for specific order options by -6%. Luminous flux value refers to inner colour traffic white, matt silver.



FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
15.2 W, 450 mA	2700 K	1660 lm	109 lm/W	0 4 8 - 3 4 0 1 9 1 <input checked="" type="checkbox"/> F
	3000 K	1710 lm	113 lm/W	0 4 8 - 3 4 0 1 0 1 <input checked="" type="checkbox"/> F
	3500 K	1750 lm	115 lm/W	0 4 8 - 3 4 0 1 2 1 <input checked="" type="checkbox"/> F
	4000 K	1790 lm	118 lm/W	0 4 8 - 3 4 0 1 1 1 <input checked="" type="checkbox"/> F

The data values for the luminaire luminous flux may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

WIDE FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
15.2 W, 450 mA	2700 K	1800 lm	118 lm/W	0 4 8 - 3 4 0 1 9 1 <input checked="" type="checkbox"/> W
	3000 K	1850 lm	121 lm/W	0 4 8 - 3 4 0 1 0 1 <input checked="" type="checkbox"/> W
	3500 K	1890 lm	124 lm/W	0 4 8 - 3 4 0 1 2 1 <input checked="" type="checkbox"/> W
	4000 K	1940 lm	127 lm/W	0 4 8 - 3 4 0 1 1 1 <input checked="" type="checkbox"/> W



SASSO 100 round adjustable semi-recessed (TW 2700K - 6500K)



MEDIUM CRI ≥ 92, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
24.2 W	tunable w.	1830 lm	76 lm/W	0 4 8 - 3 4 0 1 D 3 <input checked="" type="checkbox"/> M

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to inner colour traffic white, matt silver. DALI-2 power supply included



WIDE FLOOD CRI ≥ 92, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
24.2 W	tunable w.	1890 lm	78 lm/W	0 4 8 - 3 4 0 1 D 3 <input checked="" type="checkbox"/> W

DALI-2 power supply included

Order options

COLOUR	<input checked="" type="checkbox"/>	INNER COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	jet black	1
traffic white RAL 9016	7	matt silver	4
		traffic white	7
		gold dust	9



SASSO 100 round adjustable semi-recessed (TW 1800K - 4000K)



MEDIUM CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
27.7 W	tunable w.	2010 lm	73 lm/W	0 4 8 - 3 4 0 1 L 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M


DALI-2 power supply included

WIDE FLOOD CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
27.7 W	tunable w.	2080 lm	75 lm/W	0 4 8 - 3 4 0 1 L 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

DALI-2 power supply included

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Electrical accessories (required)

POWER SUPPLY 450 mA, PC2, -264 V AC

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
21 W non DIM	198 V AC	η 86 %	143-43-30	0 0 2 - 9 0 7 6 6
28 W DALI-2	176 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 6 7


Electrical accessories (optional)



DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10–40 V



DIN RAIL POWER SUPPLY

L-W-H (mm)	ORDER CODE
72-90-63	0 0 5 - 6 5 2 0 2 1 0

220-240 V AC | 160 W | 48 V DC constant voltage

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2, -264 V AC

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA non DIM	198 V AC	η 88 %	0 0 2 - 9 0 7 6 6 A
450 mA DALI-2	176 V AC	η 85 %	0 0 2 - 9 0 7 6 7 A
700 mA non DIM	198 V AC	η 88 %	0 0 2 - 9 0 7 7 4 A
700 mA DALI-2	176 V AC	η 85 %	0 0 2 - 9 0 7 7 6 A
650 mA non DIM	198 V AC	η 88 %	0 0 2 - 9 0 7 8 0 A
650 mA DALI-2	176 V AC	η 85 %	0 0 2 - 9 0 7 8 9 A

POWER SUPPLY PRE-WIRED with loop through function DALI-2

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA			185-30-21	0 0 2 - 9 0 7 4 7
300 mA 15 W PC2	198-264 V AC	η 87 %	185-30-21	0 0 2 - 9 0 7 7 0

Order options

COLOUR	<input checked="" type="checkbox"/>	INNER COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	jet black	1
traffic white RAL 9016	7	matt silver	4
		traffic white	7
		gold dust	9

Optical accessories (optional)



HONEYCOMB LOUVER

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 55 SASSO 100	jet black	50:3	0 0 7 - 1 9 6 5 5 9 8