

## TASK angular

suspended

**EN** Rectangular suspended luminaire, consisting of single L-shaped or rectangular elements; Luminaire housing made of aluminium – rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, tool-less height adjustment; convenient quick mounting system without tools; incl. transparent feed; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-eff. LEDs – very good colour rendering; canopy for through wiring; optional acoustic elements available


**IT** Corpo illuminante a sospensione di forma rettangolare, composto da singoli elementi a L o rettangolari; Corpo illuminante in alluminio – bordi arrotondati; forma ultrapiatta (solo 15 mm); verniciatura a polvere; cavo regolabile in altezza senza attrezzi; pratico sistema di montaggio rapido senza utensili; incl. cavo di alimentazione trasparente; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; illuminazione assolutamente omogenea; LED a risp. energ. – ottima resa cromatica; rosone per cablaggio passante; in opzione elementi acustici disponibile

### Quickinfo

4000 K  
CRI  $\geq 90$ , 3 SDCM  
up to 118 lm/W  
L95 @ 50 000 h  
DALI-2  
microprismatic (UGR  $\leq 19$ )

acoustic elements  
PET felt  
♻️ from recycled material  
up to absorption class A  
🔥 available as B-s1, d0


### Types



### Luminaire colours



### Acoustic colours




### Light distribution




DiiA® standards  
251, 252, 253




click-system



microprismatic  
(UGR  $\leq 19$ )



acoustic  
elements



CRI  $\geq 98$   
XPECTRUM

## Order options

### COLOUR TEMPERATURE

4000 K

### CONTROL

DALI-2

### LUMINAIRE COLOUR

○ pure white RAL 9010 7  
● jet black RAL 9005 8

### ACOUSTIC COLOUR

○ white W  
● marble grey D  
● felt grey G  
● black L  
● special colours p. 992 X

### LIGHT OPTIC COVER

microprismatic (UGR ≤ 19)

## Options on request



### COLOUR RENDERING INDEX

CRI ≥ 80

CRI ≥ 98 XPECTRUM

### FORM

for other configurations see  
TASK S suspended system



## TASK angular suspended



### DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
197 W	4000 K	↓ 15200 / ↑ 8050 lm	0 5 9 - 5 2 8 3 1 3 K


## TASK long angular suspended



### DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
280 W	4000 K	↓ 22480 / ↑ 11620 lm	0 5 9 - 5 2 8 4 1 3 K

## Technical data



**TASK** long angular, 280 W, 4000 K,  
direct/indirect power

### ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Suspension height	2.25 m

### CALCULATION SURFACE


Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E <sub>m</sub> )	> 500 lx
Uniformity (U <sub>0</sub> )	> 0.6

### GLARE EVALUATION

Table Classification X=4H   Y=8H   S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19



## Light distribution



microprismatic  
direct/indirect power

**LUMINOUS FLUX** value calculated for  
CRI ≥ 90, colour white, cover microprismatic

## Acoustic elements

### TASK ACOUSTIC inlay

TYPE	L-W-H (mm)	ORDER CODE
1 TASK angular suspended	1155-1155-30	0 5 9 - 5 7 9 7 1 6
2 TASK long angular suspended	1155-2346-30	0 5 9 - 5 7 9 7 1 8

