



MUSE DOUBLE LIGHT acoustic

suspended


^{EN} Luminaire body made of high quality, self-supporting, at least 50% recycled PET felt with sound absorbing properties; high quality visual and tactile surface; constructed of 2 shells to form cavities that improve acoustic performance; large sound absorbing surface; pendant fitting with cable suspension; with integrated tool-less suspension height adjustment; optimised for the illumination of 2 office workstations opposite each other; incl. transparent feed; light inset made from extruded profile for improved thermal management; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

^{IT} Corpo faro in feltro prodotto con PET riciclato per almeno il 50%, alta qualità, autoportante e con proprietà fonoassorbenti; finitura con caratteristiche estetiche e tattili di alta qualità; struttura composta da 2 gusci in modo da formare cavità per migliorare le prestazioni acustiche; ampia superficie fonoassorbente; sospeso con cavo a sospensione; altezza regolabile sull'apparecchio, senza utensili; ottimizzato per l'illuminazione di 2 postazioni di lavoro disposte l'una di fronte all'altra; incl. cavo di alimentazione trasparente; unità d'illuminazione in profilo di alluminio estruso per migliorare il bilancio termico; riflettore ad alta lucentezza con design sfaccettato; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM
 UGR ≤ 19
 fino a 107 lm/W
 L90 / 50000 h
 DALI-2
 IP20
 feltro PET
 composto da almeno il 50% di
 materiale riciclato post-consumer
 fino a classe di assorbimento
 acustico A

Types




Colore



Distribuzione della luce



DiiA® standards
 251, 252, 253




DIN EN 12464-1
 UGR ≤ 19



suitable for
 double
 workstation



sound
 absorption by
 PET felt from at
 least 50%
 recycled
 material



CRI ≥ 98
 XPECTRUM
 (optional)



MUSE DOUBLE LIGHT acoustic suspended

	CRI ≥ 80	UGR ≤ 19	cd/m² ≤ 1500	 220-240 V	 1ADDR.		
--	-------------	-------------	-----------------	---------------	------------	--	--


A	B	C	D	E
$\alpha_w = 0.65$				
 PET felt		0.65 NRC	0.62 SAA	

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
41.0 W	3000 K	4160 lm	101 lm/W	0 9 1 - 1 2 2 1 5 3 F
	4000 K	4400 lm	107 lm/W	0 9 1 - 1 2 2 1 6 3 F

Light inset colour: grey cover / chrome reflector, canopy always in white

Equivalent sound absorption area ($A_{eq} m^2$)

125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
1.03	1.43	2.1	2.67	2.87	2.87




Planning Information



MUSE DOUBLE LIGHT
41W direct, 4000K, chrome reflector


ROOM VALUES	
Room dimensions	5.4 × 4 × 3 m
Room volume	64.8 m³
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Mounting height	2.23 m



CALCULATION SURFACE	
Surface dimensions	1.6 × 0.8
Surface height	0.75 m
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
≥ 65° ≤ 1500 cd/m²	

Sound absorption coefficients



Order options

COLOUR	
anthracite	B
indigo blue	E
felt grey	G
bright blue	P

Inter-pool Immobilien GmbH

Austria

Architetto


Inter-pool Immobilien
GmbH / Architekt DI
Stephan Kopinits

Lighting Design

Inter-pool Immobilien
GmbH / Architekt DI
Stephan Kopinits

Fotografo

Schneider & Schütz
GmbH



Prodotti utilizzati



**MUSE DOUBLE
LIGHT acoustic
suspended**





Magazin auf EF

Germania

Fotografo

Alexander Schwarz



Prodotti utilizzati



**UNICO Q9 basic
recessed**



**MUSE DOUBLE
LIGHT acoustic
suspended**

