




MUSE LIGHT acoustic

suspended

^{EN} Luminaire body made of high quality, self-supporting, at least 50% recycled PET felt with sound absorbing properties; high quality visual and tactile surface; constructed of 2 shells to form cavities that improve acoustic performance; large sound absorbing surface; pendant fitting with cable suspension; with integrated tool-less suspension height adjustment; optimised for the illumination of office workstations; incl. transparent feed; light inset made from extruded profile for improved thermal management; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

^{IT} Corpo faro in feltro prodotto con PET riciclato per almeno il 50 %, alta qualità, autoportante e con proprietà fonoassorbenti; finitura con caratteristiche estetiche e tattili di alta qualità; struttura composta da 2 gusci in modo da formare cavità per migliorare le prestazioni acustiche; ampia superficie fonoassorbente; sospeso con cavo a sospensione; altezza regolabile sull'apparecchio, senza utensili; ottimizzato per l'illuminazione di postazioni di lavoro; incl. cavo di alimentazione trasparente; unità d'illuminazione in profilo di alluminio estruso per migliorare il bilancio termico; riflettore ad alta lucentezza con design sfaccettato; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM
 UGR ≤ 19
 fino a 108 lm/W
 L90 / 50000 h
 DALI-2
 IP20
 feltro PET
 composto da almeno il 50% di
 materiale riciclato post-consumer
 fino a classe di assorbimento
 acustico A

Types



Colore



Distribuzione della luce




DiiA® standards
 251, 252, 253




DIN EN 12464-1
 UGR ≤ 19



sound
 absorption by
 PET felt from at
 least 50%
 recycled
 material



CRI ≥ 98
 XPECTRUM
 (optional)



MUSE LIGHT acoustic suspended

	CRI ≥ 80	UGR ≤ 19	cd/m² ≤ 1500	220-240 V	DALI 1ADDR.		X-PERT
--	-------------	-------------	-----------------	-----------	----------------	--	--------


A	B	C	D	E
$\alpha_w = 0.45$				
		PET felt	0.55 NRC	0.55 SAA

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.3 W	3000 K	2080 lm	102 lm/W	0 9 1 - 1 2 1 1 5 3 F
	4000 K	2200 lm	108 lm/W	0 9 1 - 1 2 1 1 6 3 F


Light inset colour: grey cover / chrome reflector, canopy always in white

Equivalent sound absorption area ($A_{eq} m^2$)

125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
0.1	0.2	0.57	0.93	0.97	0.93



Planning Information




MUSE LIGHT
20 W direct, 4000K, chrome reflector
+ **MUSE BAFFLE** (every 2nd)

ROOM VALUES
Room dimensions 9 × 5 × 3 m
Room volume 135 m³
Reflection factor 0.7 | 0.5 | 0.2
Maintenance factor 0.8
Mounting height 2.23 m

CALCULATION SURFACE
Surface dimensions 8 × 4
Surface height 0.75 m
Average illuminance (E_m) > 500 lx

GLARE EVALUATION
Table Classification X=4H | Y=8H | S=0.25H
UGR transversal ≤ 19
UGR axial ≤ 19
≥ 65° ≤ 1500 cd/m²

Sound absorption coefficients



Order options

COLOUR	
anthracite	B
indigo blue	E
felt grey	G
bright blue	P

XAL Office, Vienna

Austria

Lighting Design

XAL Lighting Design

Fotografo


Kurt Kuball




Prodotti utilizzati



**MUSE DOUBLE
LIGHT** acoustic
suspended



MUSE LIGHT
acoustic suspended



MUSE BAFFLE
acoustic suspended



LENO surface



LITO 60 suspended



