



## TASK

free standing


<sup>EN</sup> Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

<sup>IT</sup> Piantana di alluminio con testata rettangolare e bordi arrotondati; forma ultrapiatta (solo 15 mm); stelo rettangolare; piedistallo con apertura per piede tavolo; verniciatura a polvere; distribuzione della luce diretta/indiretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente direzionata in basso e e su tramite incisione laser; opzionale: componente di luce indiretta con piastre proprie per un flusso luminoso potenziato; opzionale: componente di luce indiretta con piastre proprie inclinate per un'emissione asimmetrica; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; interruttore integrato nello stelo; incl. cavo di collegamento (3 m) con spina Schuko

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq 90$  / 3 SDCM  
 UGR  $\leq 10$ , UGR  $\leq 13$ , UGR  $\leq 19$   
 fino a : 4,370 lm /  $\uparrow$  11,000 lm  
 fino a 137 lm/W  
 L90 / 50000 h  
 DIM touch sul palo, Loxone Air /  
 DIM touch sul palo, Loxone Air /  
 ESSENTIAL sensor, sensore  
 ESSENTIAL autonomo  
 Microprismatic  
 IP20

### Types



### Colore



### Distribuzione della luce



suitable for  
double  
workstation




SENSE sensor  
on request




lighting control  
by touch DIM  
on pole




tunable white  
2700 – 6500 K



CRI  $\geq 98$   
**XPECTRUM**  
(optional)



## TASK free standing U-shape



### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90


| SYSTEM | COLOUR TEMP. | LUM. FLUX       | SYSTEM   | ORDER CODE            |
|--------|--------------|-----------------|----------|-----------------------|
| 71.0 W | 3000 K       | ↓4100/↑13350 lm | 105 lm/W | 0 5 9 - 2 9 4 3 0   Z |
|        | 4000 K       | ↓4370/↑13560 lm | 112 lm/W | 0 5 9 - 2 9 4 3 1   Z |

### MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90


| SYSTEM | COLOUR TEMP. | LUM. FLUX      | SYSTEM   | ORDER CODE            |
|--------|--------------|----------------|----------|-----------------------|
| 80.0 W | 3000 K       | ↓2400/↑7330 lm | 122 lm/W | 0 5 9 - 2 9 4 2 0   Z |
|        | 4000 K       | ↓2550/↑7800 lm | 129 lm/W | 0 5 9 - 2 9 4 2 1   Z |

### MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX       | SYSTEM   | ORDER CODE            |
|--------|--------------|-----------------|----------|-----------------------|
| 95.0 W | 4000 K       | ↓2030/↑11000 lm | 137 lm/W | 0 5 9 - 2 9 4 1 1   Z |
| 97.0 W | 3000 K       | ↓1900/↑10300 lm | 126 lm/W | 0 5 9 - 2 9 4 1 0   Z |



## TASK free standing T-shape



### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX       | SYSTEM   | ORDER CODE            |
|--------|--------------|-----------------|----------|-----------------------|
| 71.0 W | 3000 K       | ↓4100/↑13350 lm | 105 lm/W | 0 5 9 - 2 9 5 3 0   Z |
|        | 4000 K       | ↓4370/↑13560 lm | 112 lm/W | 0 5 9 - 2 9 5 3 1   Z |

### MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX      | SYSTEM   | ORDER CODE            |
|--------|--------------|----------------|----------|-----------------------|
| 80.0 W | 3000 K       | ↓2400/↑7330 lm | 122 lm/W | 0 5 9 - 2 9 5 2 0   Z |
|        | 4000 K       | ↓2550/↑7800 lm | 129 lm/W | 0 5 9 - 2 9 5 2 1   Z |

### MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX       | SYSTEM   | ORDER CODE            |
|--------|--------------|-----------------|----------|-----------------------|
| 95.0 W | 4000 K       | ↓2030/↑11000 lm | 137 lm/W | 0 5 9 - 2 9 5 1 1   Z |
| 97.0 W | 3000 K       | ↓1900/↑10300 lm | 126 lm/W | 0 5 9 - 2 9 5 1 0   Z |

## Order options

| CONTROL                        |   | COLOUR                   |   |
|--------------------------------|---|--------------------------|---|
| touch DIM on pole              | 5 | white aluminium RAL 9006 | 6 |
| stand alone ESSENTIAL sensor   | 7 | pure white RAL 9010      | 7 |
| Loxone Air / ESSENTIAL sensor  | S | jet black RAL 9005       | 8 |
| Loxone Air / touch DIM on pole | T | special colours          | X |

# OFFICE OMV

Austria

**Fotografo**  
Kurt Kuball



## Prodotti utilizzati



## TASK free standing

