



TASK

wall


^{EN} Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; suitable for wall mounting; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special PCBs with asymmetrical light distribution; for optimum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering

^{IT} Corpo illuminante rettangolare in alluminio con bordi arrotondati; forma ultrapiatta (solo 15 mm); verniciatura a polvere; montaggio a parete; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; direzionamento della luce con materiale del riflettore altamente riflettente; percentuale indiretta con piastre dedicate a distribuzione asimmetrica della luce; per un'illuminazione ottimale del soffitto; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM
fino a ↓ 1,970 lm / ↑ 3,760 lm
fino a 125 lm/W
L90 / 50000 h
DALI-2
Microprismatic
IP20

Types



Colore




Distribuzione della luce



asymmetrical
ceiling
illumination




TASK wall




MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
46.0 W	3000 K	↓1850/↑3530 lm	117 lm/W	0 5 9 - 2 0 3 2 0 3 Z
	4000 K	↓1970/↑3760 lm	125 lm/W	0 5 9 - 2 0 3 2 1 3 Z



Planning Information



TASK wall
46 W, 4000 K, direct / indirect power

ROOM VALUES	
Room dimensions	5.4 × 4.0 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Mounting height	2.25 m

CALCULATION SURFACE	
Surface dimensions	Floor
Surface height	0 m

GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8