

UNICO

wall recessed

EN Recessed wall luminaire in aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; installation possible in different housings; surface powder coated; incl. external converter; high-quality reflector with micro-faceted, aluminum-vaporised surface; different asymmetrical light distributions; installation optionally for floor or ceiling illumination; energy-efficient high power LEDs with very good colour rendering

IT App. a incasso da parete in allum.; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); incasso possibile in vari telai; verniciatura a polvere; incl. convertitore esterno; riflettore di alta qualità con superficie a microfacette e vaporizzata in alluminio; diverse distribuzioni di luce asimmetriche; montaggio per illum. pavimento o soffitto a scelta; LED high power a risparmio energetico con ottima resa cromatica

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 45 lm/W
 L90 @ 50 000h
 non DIM, DALI-2

Types



Colours



Light distribution



homogeneous floor illumination



safety glass for dust protection



tunable white 2700–5000K

Order options

| COLOUR TEMPERATURE | |
|--------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

| LIGHT OPTIC | |
|-------------|--|
| wide floor | |


| MATERIAL COLOUR | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | W |
| <input checked="" type="radio"/> jet black RAL 9005 | B |

Options on request

| COLOUR TEMPERATURE | |
|--------------------------|--|
| tunable white 2700–5000K | |

only available for 2 lamps | DALI-2 DT8


Light distribution





microprismatic
direct/indirect power

LUMINOUS FLUX value calculated for
3000K, CRI ≥ 90, colour white, reflector chrome
2700K -6%, 4000K +7%

UNICO wall recessed




| | | | |
|---------------|---------------------|----------------------|-------------------|
| 1 LAMP | SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
| | 9.9 W | 435 lm | 090-6L1::UB001 |




| | | | |
|----------------|---------------------|----------------------|-------------------|
| 2 LAMPS | SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
| | 17.2 W | 777 lm | 090-6L2::UB001 |

Accessories



MOUNTING SET WITH TRIM
for intermediate ceilings 2–25 mm

| TYPE | L-W-H (mm) | CUTOUT (mm) | ORDER CODE |
|---------|------------|-------------|------------|
| 1 lamp | 101-63-20 | 90-50 | 090-7L2020 |
| 2 lamps | 101-101-30 | 90-90 | 090-7Q4020 |



TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25 mm

| TYPE | L-W-H (mm) | CUTOUT (mm) | ORDER CODE |
|---------|------------|-------------|-------------|
| 1 lamp | 88-50-47 | 90-50 | 090-7L20100 |
| 2 lamps | 85-85-47 | 90-90 | 090-7Q40100 |

PRIMED CONCRETE MOUNTING SET

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------------------|-------------|-------------|
| primed concrete ceilings | 240-400-130 | 052-1914320 |

order mounting set separately

EXPOSED CONCRETE MOUNTING SET

| TYPE | ORDER CODE |
|--------------------------|-------------|
| 1 lamp exposed concrete | 090-6L10500 |
| 2 lamps exposed concrete | 090-6L20600 |

order mounting set separately

Planning information

