



## MITA square

recessed with trim


EN Square luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high-gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante quadrato in pressofusione di alluminio; forma estremamente sottile; apparecchio da incasso con bordo perimetrale; in opzione: copertura cieca per l'inserimento nel vano interno disponibile come accessorio; per soffitti di spessore 2-25 mm; verniciatura a polvere; riflettore ad alta lucentezza con design sfaccettato; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K, TW  
 CRI ≥ 80, CRI ≥ 90, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 1500 cd/m<sup>2</sup>  
 up to 160 lm/W  
 L95 @ 50 000 h  
 DALI-2  
 reflector (UGR ≤ 19)

### Types



### Colours




### Light distribution



suitable for plaster-board or grid ceilings



DIN EN 12464-1  
 UGR ≤ 19



tunable white  
 2700-6500 K

### Order options

#### COLOUR TEMPERATURE

3000 K (CRI ≥ 90)	0
4000 K (CRI ≥ 90)	1
3000 K (CRI ≥ 80)	5
4000 K (CRI ≥ 80)	6
tunable white 2700–6500 K*	

\*DALI-2 DT8, CRI ≥ 90

#### CONTROL

DALI-2

#### MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

#### REFLECTOR COLOUR

✓ chrome	R
● dark chrome	B


#### LIGHT OPTIC COVER

reflector (UGR ≤ 19)

### Options on request

#### GRID CEILING MOUNTING

installed in module 600 × 600 mm  
 installed in module 625 × 625 mm




### MITA square 200 trim



#### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.8 W	3000 K	1950 lm	074-8314::3
14.2 W	4000 K	2220 lm	
	2700–6500 K	1690 lm	074-8314D3



### MITA square 360 trim



#### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4210 lm	074-8316::3
28.5 W	4000 K	4790 lm	
40 W*	2700–6500 K	3370 lm	074-8316D3
	3000 K	5470 lm	074-8326::3
	4000 K	6230 lm	


\*not for tunable white

### Accessories

#### BLIND COVER

TYPE	ORDER CODE
MITA 200 square recessed	074-891341
MITA 360 square recessed	074-891361

### Light distribution



reflector (UGR ≤ 19)  
 direct

LUMINOUS FLUX value calculated for  
 CRI ≥ 80, colour white, reflector chrome