



VELA

suspended


EN Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface powder coated; suspended; with integrated tool-less suspension height adjustment; incl. feeder cable or with height adjustable rod suspension (chrome), feed in rod; highly reflective coating of the PCB for improved efficiency; completely homogeneously illuminated, satinised PMMA cover; up to ø600 mm: microprismatic PMMA cover; either with direct or direct / indirect light distribution; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; energy-efficient LEDs with very good colour rendering; canopy with 2 cable openings and plug-in terminal for through wiring

IT Corpo illuminante rotondo in profilo di alluminio rullato, senza punti di saldatura; verniciatura a polvere; sospeso; altezza regolabile sull'apparecchio, senza utensili; incl. cavo di alimentazione o con asta di sospensione accorciabile (cromata), cavo alimentazione nell'asta di sospensione; rivestimento altamente riflettente della scheda per un rendimento migliore; diffusore satinato in PMMA a illuminazione assolutamente omogenea; fino a ø 600 mm: rifrattore a microprismi in PMMA; a scelta con emissione diretta oppure diretta/indiretta; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; LED ad efficienza energetica con elevata resa cromatica; rosone con 2 ingressi cavi e morsetto per cablaggio passante

Quickinfo

3000 K, 4000 K, TW
 CRI ≥ 80, 3 SDCM
 UGR ≤ 19 / 65° ≤ 3000 cd/m²
 up to 20600 / ± 6060 lm
 up to 148 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2
 opal, microprismatic
 IP 40


Types




Colours



Light distributions




DiiA® standards
 251, 252, 253




DIN EN 12464-1
 UGR ≤ 19



direct/indirect
 illumination



tunable white
 2700–6500 K



CRI ≥ 98
 XPECTRUM

Order options

SUSPENSION

cable 1500 mm	2
rod 1000 mm	4

COLOUR TEMPERATURE

3000 K	5
4000 K	6
tunable white 2700–6500 K*	

*DALI-2 DT8

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours*	X

*canopy always in white

LIGHT OPTIC COVER

opal high performance	O
microprismatic (UGR ≤ 19)	K

Options on request

COLOUR RENDERING INDEX

CRI ≥ 90	
CRI ≥ 98 XPECTRUM	


SUSPENSION

rod 2000 mm	
-------------	--




EMERGENCY LIGHT

1h accupack	
3h accupack	

Light distributions

opal high performance
direct/indirect powermicroprismatic
direct/indirect power

LUMINOUS FLUX value calculated for
4000 K, CRI ≥ 80, colour white, cover opal
3000 K - 5%



VELA 450 suspended



DIRECT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
16.7 W	2170 lm	0 7 3 - 1 4 1 : : 3 4
30 W	3620 lm	0 7 3 - 1 4 2 : : 3 4 O
30 W TW	2700–6500 K	0 7 3 - 1 4 4 2 D 3 4

DIRECT / INDIRECT POWER

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
21.1 W	↓ 2070 / ↑ 812 lm	0 7 3 - 1 4 4 : : 3 4
35 W	↓ 3250 / ↑ 1270 lm	0 7 3 - 1 4 5 : : 3 4 O
36 W TW	2700–6500 K ↓ 3190 / ↑ 1250 lm	0 7 3 - 1 4 4 5 D 3 4

VELA 600 suspended



DIRECT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
31 W	4250 lm	0 7 3 - 1 4 5 1 : : 3 4
48 W	6290 lm	0 7 3 - 1 4 5 2 : : 3 4 O
51 W TW	2700–6500 K	0 7 3 - 1 4 5 2 D 3 4

DIRECT / INDIRECT POWER

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
45 W	↓ 4350 / ↑ 1970 lm	0 7 3 - 1 4 5 4 : : 3 4
68 W	↓ 6290 / ↑ 2850 lm	0 7 3 - 1 4 5 5 : : 3 4 O
62 W TW	2700–6500 K ↓ 5630 / ↑ 2540 lm	0 7 3 - 1 4 5 5 D 3 4

VELA 900 suspended



DIRECT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
71 W	9520 lm	0 7 3 - 1 2 7 1 : : 3 4

DIRECT / INDIRECT POWER

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
96 W	↓ 9520 / ↑ 4670 lm	0 7 3 - 1 2 7 4 : : 3 4

VELA 1200 suspended



DIRECT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
147 W	20600 lm	0 7 3 - 1 2 8 1 : : 3 4



DIRECT / INDIRECT POWER

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
185 W	↓ 20600 / ↑ 6060 lm	0 7 3 - 1 2 8 4 : : 3 4