



## FLOW

surface


**EN** Square aluminium luminaire housing, flat design (luminaire housing 35 mm); surface powder coated; suitable for wall or ceiling mounting, luminaire housing set 11 mm away from wall or ceiling; convenient quick mounting system without tools; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; completely homogeneous illumination; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**IT** Corpo illuminante quadrato in alluminio, forma piatta (corpo illuminante 35 mm); verniciatura a polvere; per montaggio a parete o soffitto, distanza corpo illuminante da parete o soffitto 11 mm; pratico sistema di montaggio rapido senza utensili; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; direzionamento della luce con materiale del riflettore altamente riflettente; illuminazione assolutamente omogenea; stessa luminosità nei modelli di tutte le dimensioni; LED ad efficienza energetica con elevata resa cromatica; apparecchio con 2 ingressi cavi e morsetto per cablaggio passante

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80, 3 SDCM  
 up to 146 lm/W  
 L90 @ 50 000 h  
 non DIM, DALI-2  
 opal, IP 40

### Types



### Colours



### Light distribution



**DiiA® standards**  
 251, 252, 253



easy mounting by  
 click-mechanism



insect protection  
 (IP 40)

## Order options

COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL	
non DIM	1
DALI-2	3


MATERIAL COLOUR	
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours ● p. 992	X

LIGHT OPTIC COVER	
opal	

## Options on request

MOUNTING	
1500 mm cable suspension	

COLOUR RENDERING INDEX	
CRI ≥ 90	




### FLOW 320 surface



#### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.2W	3000K	2000lm	0 7 3 - 0 1 3 1 :: ◆ ◆ □ O
	4000K	2120lm	




### FLOW 450 surface



#### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.9W	3000K	3250lm	0 7 3 - 0 1 4 1 :: ◆ ◆ □ O
	4000K	3440lm	



### FLOW 600 surface



#### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
44W	3000K	6060lm	0 7 3 - 0 1 5 1 :: ◆ ◆ □ O
	4000K	6420lm	

## Accessories

TYPE	ORDER CODE
dismounting tool	0 7 3 - 0 1 0 0 0 0