



CAVO round/square

recessed

^{EN} Recessed housing made of pressed steel sheet for flush installation in plasterboard ceilings, underside of aluminium-reinforced plaster; alternatively with round or square cut-out; no break-out of edges; 3 cylindrical spotlight heads can be installed without tools by means of magnetic holders; simple electrical connection of the spotlights due to non-reversible plug and play connection; housing and spotlights powder coated; optionally: indirect light component in housing; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; good glare reduction due to recessed light point plane; high quality lens system; precise radiation characteristic; optical attachments as accessories; hot plug protection

^{IT} Telaio da incasso in lamiera d'acciaio per incasso a scomparsa in soffitti in cartongesso, lato inferiore in gesso rinforzato con alluminio; a scelta con sagoma rotonda o quadrata; a scelta con sagoma rotonda o quadrata; nessuna rottura dei bordi; 3 faretti cilindrici montabili senza utensili tramite fissaggio magnetico; collegamento elettrico dei faretti semplificato dal sistema Plug & Play a prova di polarizzazione inversa; housing e faretti verniciati a polvere; in opzione: luce indiretta; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica; ottima schermatura con superficie di emissione arretrata; ottica lenticolare di qualità; emissione precisa; unità ottiche come accessori; protezione hot plug

Quickinfo


2700 K, 3000 K
CRI ≥ 90, 2 SDCM
DALI-2

L80 @ 50 000 h
mounting housing with glowing

L90 @ 50 000 h
JUST 45 up to 69 lm/W

L95 @ 50 000 h
JUST 32 focus up to 3×54 lm/W

Types



Housing colours



Inset colours



Light distributions



magnetic holders for
tool-free mounting



optical
accessories

Order options

COLOUR TEMPERATURE	☼☼
2700K	4
3000K	5

CONTROL	
DALI-2	

INSET COLOUR	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● gold dust RAL 260-M	9


HOUSING COLOUR	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE	▲
medium 23°	M
flood 44°	F

Options on request

OPTICAL ACCESSORIES

elliptical sculpture foil
 snoot
 colour filter (red, blue, green, etc.)
 only for JUST 32 focus



JUST 32 focus 17–43°



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
4.6 W	250 lm	0 4 9 - 8 2 1 1 ☼☼ ☑
not for single use		

JUST 45



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.8 W	640 lm	0 4 9 - 8 3 0 2 ☼☼ ☑▲

Mounting accessories

MOUNTING HOUSING 1 DALI-2 address

for trimless installation in plasterboard ceilings 8-25 mm

TYPE	L-W-H (mm)	ORDER CODE
round 3 spots (▲ 4.5 kg)	260:260:120	0 4 9 - 8 8 0 3 0 3 ■
square 3 spots (▲ 4.5 kg)	260:260:120	0 4 9 - 8 8 1 3 0 3 ■

incl. power supply 220–240 V AC, 50–60 Hz, ⚡ PC I, ENEC approved

MOUNTING HOUSING WITH GLOWING (3000 K) 2 DALI-2 addresses

for trimless installation in plasterboard ceilings 8-25 mm

TYPE	L-W-H (mm)	ORDER CODE
round 3 spots (▲ 4.5 kg)	260:260:120	0 4 9 - 8 8 2 3 5 3 7
square 3 spots (▲ 4.5 kg)	260:260:120	0 4 9 - 8 8 3 3 5 3 7

incl. power supply 220–240 V AC, 50–60 Hz, ⚡ PC I, ENEC approved

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
JUST 32 focus	30·4	0 0 7 - 1 9 6 5 1 7 8
JUST 45	42·3	0 0 7 - 1 9 6 5 1 8 8

INSET POWER is the current

consumption excluding any ballast

LUMINOUS FLUX value calculated for

3000K, CRI ≥ 90, colour white, lens medium

2700K -5%



CAVO linear

recessed

EN Installation housing in pressed steel sheet with rectangular cut-out; for trimless installation in plasterboard ceilings; special edge design with perforations for better adhesion of filler; or with trim; 3 or 6 cylindrical spotlight heads can be installed without tools by means of magnetic holders; simple electrical connection of the spotlights due to non-reversible plug and play connection; housing and spotlights powder coated; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; good glare reduction due to recessed light point plane; high quality lens system; precise radiation characteristic; optical attachments as accessories; hot plug protection

IT Cassaforma in lamiera d'acciaio con sagoma rettangolare; incasso a scomparsa in soffitti di cartongesso; bordatura speciale forata per una migliore aderenza dello stucco; o con bordo perimetrale; 3 o 6 faretti cilindrici montabili senza utensili tramite fissaggio magnetico; collegamento elettrico dei faretti semplificato dal sistema Plug & Play a prova di polarizzazione inversa; housing e faretti verniciati a polvere; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica; ottima schermatura con superficie di emissione arretrata; ottica lenticolare di qualità; emissione precisa; unità ottiche come accessori; protezione hot plug


Quickinfo

2700 K, 3000 K
CRI ≥ 90, 2 SDCM
DALI-2

L90 @ 50 000 h
JUST 45 up to 6×69 lm/W

L95 @ 50 000 h
JUST 32 focus up to 6×54 lm/W

Types



Housing colours



Inset colours



Light distributions



magnetic holders for tool-free mounting



optical accessories

Order options

COLOUR TEMPERATURE	☼☼
2700K	4
3000K	5

CONTROL	
DALI-2	

INSET COLOUR	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● gold dust RAL 260-M	9


HOUSING COLOUR	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE	▲
medium 23°	M
flood 44°	F

Options on request

OPTICAL ACCESSORIES

elliptical sculpture foil
 snoot
 colour filter (red, blue, green, etc.)
 only for JUST 32 focus



JUST 32 focus 17–43°



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
4.6 W	250 lm	0 4 9 - 8 2 1 1 ☼☼☑
not for single use		



JUST 45



SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.8 W	640 lm	0 4 9 - 8 3 0 2 ☼☼☑▲

Mounting accessories

TRIMLESS MOUNTING HOUSING

for trimless installation in plasterboard ceilings 12.5 mm

TYPE	L-W-H (mm)	ORDER CODE
for 3 spots (▲ 2.4 kg), 1 DALI	308-252-120	0 4 9 - 8 8 4 3 0 3 ■
for 6 spots (▲ 3.6 kg), 2 DALI	608-269-120	0 4 9 - 8 8 4 6 0 3 ■

incl. power supply 220–240 V AC, 50–60 Hz, ⚡ PC I, ENEC approved

MOUNTING HOUSING WITH TRIM

for intermediate ceilings 12.5 mm

TYPE	L-W-H (mm)	ORDER CODE
for 3 spots (▲ 2.7 kg), 1 DALI	344-254-120	0 4 9 - 8 8 5 3 0 3 ■
for 6 spots (▲ 4.7 kg), 2 DALI	644-271-120	0 4 9 - 8 8 5 6 0 3 ■

incl. power supply 220–240 V AC, 50–60 Hz, ⚡ PC I, ENEC approved

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
JUST 32 focus	30-4	0 0 7 - 1 9 6 5 1 7 8
JUST 45	42-3	0 0 7 - 1 9 6 5 1 8 8

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white, lens medium 2700K -5%