

## 049-6120417S 002-90743



## Appunti

Quantità / Data



Soffitto | Semi-incasso

orientabile max 90°

rotazione 350°

bianco | RAL 9016 <sup>1</sup>

IP20

754 lm

## 2700 K

CRI  $\geq 90$

L80 / 50

L80 / 50000 h

MacAdam iniziale  $\leq 2$  SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>{1-15}</sub>: 89

MR 0.53 | MDER 0.48

## spot | angolo del fascio 18°

$$\text{PstLM} \leq 1.0^{2\ 3\ 4\ 5} \mid \text{SVM} \leq 0.4^{2\ 3\ 4\ 5}$$

DALI-2 | 1 DALI Addr.

classe isolamento 2 | 220-240 V

sistema 11.6 W | apparecchio 8.7 W

apparecchio 86 lm/W <sup>6</sup>

36 Vf | 250 mA

diametro 32 mm | altezza 139 mm

0.39 kg

diametro 46 mm


spessore min. del soffitto 2 mm | spessore max.  
del soffitto 25 mm

profondità di incasso 110 mm

spot 18°

h (m)	E0° (lx)	ø (m)
1	5710	0.32
2	1430	0.63
3	630	0.95
4	360	1.27
5	230	1.58

## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

