

# ARY cable suspended canopy surface

049-521161XM 005-2602197



Progetto / Tipo \_\_\_\_\_

Appunti \_\_\_\_\_

Quantità / Data \_\_\_\_\_



## Generale

Soffitto , Sospeso \_\_\_\_\_

colori speciali \_\_\_\_\_

Rosone bianco traffico \_\_\_\_\_

IP20 \_\_\_\_\_

739 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam iniziale  $\leq$  3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 89 , R<sub>t(1-15)</sub>: 87 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.73 \_\_\_\_\_

## Ottico

medium \_\_\_\_\_

angolo del fascio 25° \_\_\_\_\_

## Dati elettrici

Casambi \_\_\_\_\_

11.2 W \_\_\_\_\_

classe isolamento 2 220-240V \_\_\_\_\_

66 lm/W \_\_\_\_\_

## Dati fisici


sospensione 2000 mm con gancio \_\_\_\_\_

diametro 47 mm \_\_\_\_\_

altezza 110 mm \_\_\_\_\_

0.4 kg \_\_\_\_\_


## Distribuzione della luce



medium 25°

h (m)	EO° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

