



SASSO 60/100 round

ceiling

^{EN} Cylindrical ceiling mounted spotlight made of aluminium, available in 2 sizes; light inset lacquered; housing powder coated; luminaire housing can be attached to mounting plate without tools by interlock; adj. sym. or asym. radiation characteristic; variants with sym. radiation characteristic; variants with asym. radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE); no multiple shadows; efficient LEDs with very good colour rendering; converter integrated into spotlight head

^{IT} Faretto cilindrico in alluminio montato sul soffitto, due misure; inserto verniciato; housing verniciato a polvere; corpo illuminante montabile ad appoggio senza attrezzi su piastra di montaggio tramite blocco di sicurezza; emissione simm. o asim. regolabile; varianti emiss. simm.: precisa grazie all'ottica lenticolare; varianti con emiss. asim.: riflettore di qualità con superficie vaporizzata in alluminio micro-sfaccettata; tecnologia COB (Chip on Board) per la massima efficienza (ADJUSTABLE); assenza di ombre multiple; LED efficienti con alta resa cromatica; converter integrato nella testata del faretto

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 2 SDCM
 SASSO 60 up to 81lm/W
 SASSO 100 up to 100lm/W
 L80 @ 50000h
 non DIM, DALI-2

Types

ceiling



Housing colours



Inset colours



Light distributions

SASSO 60



SASSO 100



wallwasher and
ww floor inset



glare control
(UGR ≤ 16)



easy mounting;
no visible screws



CWD
1800–3000K



CRI ≥ 95
2 SDCM

Order options

COLOUR TEMPERATURE	☐☐
2700 K	4
3000 K	5
4000 K	6

CONTROL	◆
non DIM	1
DALI-2	3

HOUSING COLOUR	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	1

INSET COLOUR	■
○ traffic white RAL 9016 (UGR _{≤22})	7
● matt silver (UGR _{≤19})	4
● jet black RAL 9005 (UGR _{≤16})	1
● gold dust RAL 260-M (UGR _{≤19})	9

BEAM ANGLE SASSO 60	▲
spot 11°	S
medium 21°	M
flood 42°	F
wide flood 54°	W

BEAM ANGLE SASSO 100	▲
spot 19°	S
medium 34°	M
flood 45°	F
wide flood 65°	W

Options on request

COLOUR RENDERING INDEX
CRI ≥ 95, 2 SDCM

COLOUR TEMPERATURE
CWD 1800–3000 K
not for WW & WWF version

BEAM ANGLE SASSO 100
super wide flood 70°



SASSO 60 round ceiling



ADJUSTABLE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.6 W	2700 K	808 lm	0 4 8 - 3 1 1 0 ☐☐◆◆☑■▲
	3000 K	874 lm	
	4000 K	939 lm	



WALLWASHER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.4 W	2700 K	635 lm	0 4 8 - 3 7 1 0 ☐☐◆◆☑■▲
	3000 K	635 lm	
	4000 K	744 lm	

WALLWASHER/FLOOR

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.4 W	2700 K	633 lm	0 4 8 - 3 7 1 0 ☐☐◆◆☑■▲W
	3000 K	633 lm	
	4000 K	746 lm	

SASSO 100 round ceiling



ADJUSTABLE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
20.2 W	2700 K	1650 lm	0 4 8 - 3 4 1 0 ☐☐◆◆☑■▲
	3000 K	1790 lm	
	4000 K	1930 lm	

