

SASSO 60/100 square

semi-recessed

EN Square semi-recessed spotlight made of aluminium, available in 2 sizes; light inset lacquered; housing powder coated; luminaire housing can be attached to mounting plate without tools by interlock; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with sym. radiation characteristic: precise due to high quality lens system; variants with asym. radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable

IT Faretto quadrato in alluminio con montaggio a semincasso, due misure; inserto verniciato; housing verniciato a polvere; corpo illuminante montabile ad appoggio senza attrezzi su piastra di montaggio tramite blocco di sicurezza; a scelta orientabile / fisso simmetrico o asimmetrico caratteristiche di emissione; varianti emiss. simm.: precisa grazie all'ottica lenticolare; varianti con emiss. asimmm.: riflettore di qualità con superficie vaporizzata in alluminio micro-sfaccettata; tecnologia COB (Chip on Board) per la massima efficienza (ADJUSTABLE e DOWNLIGHT); assenza di ombre multiple; LED efficienti con alta resa cromatica; converter esterno da inserire nel soffitto, cablaggio passante adatto

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 2 SDCM
 SASSO 60 up to 86lm/W
 SASSO 100 up to 119lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types



Housing colours



Inset colours



Light distributions

SASSO 60



SASSO 100



wallwasher and
ww floor inset



glare control
(UGR ≤ 16)



easy mounting;
no visible screws



CWD
1800–3000 K



CRI ≥ 95
2 SDCM

Order options

COLOUR TEMPERATURE

| | |
|-------|---|
| 2700K | 4 |
| 3000K | 5 |
| 4000K | 6 |

HOUSING COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 1 |

INSET COLOUR

| | |
|------------------------------------------------|---|
| ○ traffic white RAL 9016 (UGR _{≤22}) | 7 |
| ● matt silver (UGR _{≤19}) | 4 |
| ● jet black RAL 9005 (UGR _{≤16}) | 1 |
| ● gold dust RAL 260-M (UGR _{≤19}) | 9 |

BEAM ANGLE SASSO 60

| | |
|----------------|---|
| spot 11° | S |
| medium 21° | M |
| flood 42° | F |
| wide flood 54° | W |

BEAM ANGLE SASSO 100

| | |
|----------------|---|
| spot 19° | S |
| medium 34° | M |
| flood 45° | F |
| wide flood 65° | W |

Options on request

COLOUR RENDERING INDEX

CRI ≥ 95, 2 SDCM

COLOUR TEMPERATURE

CWD 1800–3000K


not for WW & WWF version

CONTROL


Casambi

BEAM ANGLE SASSO 100

super wide flood 70°



SASSO 60 square semi-recessed



DOWNLIGHT

| | | |
|--------------------|----------------------|-------------------|
| INSET POWER | LUMINOUS FLUX | ORDER CODE |
| 10.7W 36Vf 300mA | 1100lm | 048-3001::1■▲▲ |



WALLWASHER

| | | |
|--------------------|----------------------|-------------------|
| INSET POWER | LUMINOUS FLUX | ORDER CODE |
| 8.2W 27Vf 300mA | 635lm | 048-3601::1■▲A |

WALLWASHER/FLOOR

| | | |
|--------------------|----------------------|-------------------|
| INSET POWER | LUMINOUS FLUX | ORDER CODE |
| 8.2W 27Vf 300mA | 633lm | 048-3601::1■▲W |


SASSO 100 square semi-recessed



ADJUSTABLE

| | | |
|--------------------|----------------------|-------------------|
| INSET POWER | LUMINOUS FLUX | ORDER CODE |
| 17.2W 36Vf 500mA | 1890lm* | 048-3301::1■▲▲ |

*reflector wide flood



Electrical accessories

POWER SUPPLY 220-240V AC 50-60Hz, PC II

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|-----------------|------------|------------|------------|
| 300mA non DIM | η 85% | 85-40-22 | 002-90771 |
| 300mA DALI-2 | η 88% | 143-43-30 | 002-90762 |
| 500mA non DIM | η 88% | 143-43-30 | 002-90777 |
| 500mA DALI-2 | η 88% | 143-43-30 | 002-90779 |

THROUGH WIRING CONNECTION BOX for SASSO 100

| TYPE | L-W-H (mm) | ORDER CODE |
|-----------------------|------------|-------------|
| non DIM cable ø4–12mm | 105-58-30 | 005-2531110 |
| DALI cable ø4–12mm | 105-58-30 | 005-2551110 |

DIN RAIL COMPONENTS

| TYPE | W-H-D (mm) | ORDER CODE |
|-------------------------------------------------------------------------------------------------------------------|------------|-------------|
| POWER SUPPLY 220-240V AC 160W 48V DC constant voltage | 72-90-63 | 005-6520210 |
| LED DRIVER DALI-2 DT6 1–2 addr. 200–1050mA settable const. current 2×42W 48V DC U _{OUT} 10–40V | 36-88-59 | 005-6121030 |

for more details and components see page 981

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white, flood 2700K -5%, 4000K +5%