

SASSO 100 round adjustable

trim

048-2720611F 048-279631G 002-90774



Progetto / Tipo
Appunti
Quantità / Data



↑ IP20 ↓ IP40	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

Generale

Soffitto , Incasso
orientabile max 30°
rotazione 360°
nero , RAL9005 ¹
Set di montaggio grigio-argento
fronte IP40 , retro IP20
2210 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R _g : 97 , R _r : 90 , R ₍₁₋₅₎ : 89
MR 0.81
MDER 0.74

Ottico

flood
angolo del fascio 45°
UGR < 16 , ≥65° <3000 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Dati elettrici

non DIM
29.2 W
classe isolamento 2 220-240V
76 lm/W

Dati fisici


bordo
diametro 118 mm
altezza 95 mm
0.44 kg

Sagoma


diametro 108 mm
spessore min. del soffitto 2 mm
spessore max. del soffitto 25 mm
profondità di incasso 100 mm

¹ Codice RAL
² Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



Disegno prodotto



Istruzioni di montaggio



Calcolatore di illuminazione

