

SASSO 100 round downlight

trimless

048-2700614M 048-2796117 002-90776



Progetto / Tipo
Appunti
Quantità / Data



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

Generale

Soffitto , Incasso
argento opaco
fronte IP44 , retro IP20
2060 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₁₅₎ : 89
MR 0.81
MDER 0.74

Ottico

medium
angolo del fascio 33°
UGR < 16 , ≥65° <3000 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Dati elettrici

DALI-2
29.2 W
classe isolamento 2 220-240V
71 lm/W
1 DALI Addr.

Dati fisici


senza bordo
diametro 105 mm
altezza 75 mm
0.52 kg

Sagoma


diametro 106 mm
spessore min. del soffitto 12.5 mm
spessore max. del soffitto 25 mm
profondità di incasso 80 mm

¹ Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



Disegno prodotto



Istruzioni di montaggio



Calcolatore di illuminazione

