

# SASSO 100 round downlight

trimless

048-2700519F 048-2796117 002-90776



Progetto / Tipo

Appunti

Quantità / Data



## Generale

Soffitto , Incasso

dorato , RAL260-M<sup>1</sup>

fronte IP44 , retro IP20

2140 lm

## LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

MacAdam iniziale  $\leq 2$  SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

## Ottico

flood

angolo del fascio 44°

UGR  $< 16$  ,  $\geq 65^\circ < 3000$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$ <sup>2</sup>

SVM  $\leq 0.4$ <sup>2</sup>

## Dati elettrici

DALI-2

29.2 W

classe isolamento 2 220-240V

73 lm/W

1 DALI Addr.

## Dati fisici

senza bordo

diametro 105 mm

altezza 75 mm

0.52 kg

## Sagoma

diametro 106 mm

spessore min. del soffitto 12.5 mm


spessore max. del soffitto 25 mm

profondità di incasso 80 mm


<sup>1</sup> Codice RAL

<sup>2</sup> Valore del prodotto contenitore a pieno carico (non regolato)

## Distribuzione della luce



## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

