

SASSO 60 square downlight

trimless

048-2612614M 048-2697117 002-90762



Progetto / Tipo
Appunti
Quantità / Data



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

Generale

Soffitto , Incasso
argento opaco
fronte IP44 , retro IP20
1100 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₁₅₎ : 89
MR 0.81
MDER 0.74

Ottico

medium
angolo del fascio 21°
UGR < 16 , ≥65° <3000 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Dati elettrici

DALI-2
12.6 W
classe isolamento 2 220-240V
87 lm/W
1 DALI Addr.

Dati fisici


senza bordo
lunghezza 72 mm
larghezza 72 mm
altezza 48 mm
0.28 kg

Sagoma


lunghezza 73 mm
larghezza 73 mm
spessore min. del soffitto 12.5 mm
spessore max. del soffitto 25 mm
profondità di incasso 105 mm

¹ Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



Disegno prodotto



Istruzioni di montaggio



Calcolatore di illuminazione

