

SASSO 60 round downlight

trimless

048-2602611F 048-2696117 002-90771



Progetto / Tipo
Appunti
Quantità / Data



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

Generale

Soffitto , Incasso
rotazione 360°
nero , RAL9005 ¹
Set di montaggio bianco traffico
fronte IP44 , retro IP20
1000 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R _g : 97 , R _f : 90 , R _{t(1-5)} : 89
MR 0.81
MDER 0.74

Ottico

flood
angolo del fascio 41°
UGR < 16 , ≥65° <1500 cd/m ²
P _{stLM} ≤ 1.0 ²
SVM ≤ 0.4 ²

Dati elettrici

non DIM
12.6 W
classe isolamento 2 220-240V
79 lm/W

Dati fisici


senza bordo
diametro 73 mm
altezza 48 mm
0.22 kg

Sagoma

diametro 73 mm
profondità di incasso 60 mm

¹ Codice RAL
² Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



Disegno prodotto

