



CORNER

surface


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; suitable for wall or ceiling mounting; with double-sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante in profilo di alluminio estruso, modello squadrato; nessuna vite visibile; verniciatura a polvere; profilo consegnabile in anticipo; per montaggio a parete o soffitto; con emissione bilaterale; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000K
CRI ≥ 80, 3 SDCM
up to 131lm/W
L90 @ 50000h
non DIM
opal

Types




Colours



Light distribution



wall/ceiling
illumination



tunable white
2700–5000K

Order options

COLOUR TEMPERATURE

3000K

CONTROL

non DIM

MATERIAL COLOUR

- pure white (RAL 9010) 7
- white aluminium (RAL 9006) G
- jet black (RAL 9005) 8

LIGHT OPTIC COVER

opal high performance

Options on request

SYSTEM SOLUTION

installation channel, etc.

COLOUR TEMPERATURE


4000K

tunable white 2700–6500K*

*DALI-2 DT8

CONTROL

DALI-2



CORNER surface




MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
13.8W	3000K	1810lm	588	040-895251
20.7W	3000K	2720lm	888	040-895351
27.6W	3000K	3620lm	1188	040-895451
55W	3000K	7250lm	2358	040-895851
81W	3000K	9830lm	3014	040-895951

HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
20.2W	3000K	2460lm	588	040-896251
30W	3000K	3690lm	888	040-896351
40W	3000K	4910lm	1188	040-896451
71W	3000K	9340lm	2358	040-896851
98W	3000K	12700lm	3014	040-896951

Light distribution



asymmetric

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, cover opal