

SPIO 60

recessed

^{EN} Round recessed spotlight in die-cast aluminium; installation without tools in mounting set with ball catch system or with magnetic attachment; for trimless installation in plasterboard ceilings; paintable cover; shadow joint between cover and mounting set optionally fillable; choice of adjustable or fixed symmetric radiation characteristic; high quality lens system; uncluttered ceiling look through recessed lighting level; reduced light-emitting surface (only $\varnothing 10$ mm); no multiple shadows; efficient LEDs with very good colour rendering

^{IT} Faretto da incasso rotondo in alluminio pressofuso; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili o con attacco magnetico; incasso a scomparsa in soffitti di cartongesso; piastra verniciabile; giunto nascosto tra la piastra e il set di montaggio stuccabile a scelta; emissione a scelta regolabile o fissa simmetrica; ottica lenticolare di qualità; superficie di emissione arretrata per un soffitto di aspetto armonioso; superficie di emiss. ridotta (solo $\varnothing 10$ mm); assenza di ombre multiple; LED efficienti con alta resa cromatica

Quickinfo

2700 K, 3000 K
CRI ≥ 90 / 3 SDCM
UGR ≤ 10
fino a 61 lm/W
L85 / 50000 h, L95 / 50000 h
DALI-2
front IP20

Types



Colore



Set di montaggio



Distribuzione della luce



10 mm light
output area



for trimless
installation



LFO lens
technology



paintable cover




SPIO 60 downlight




FLOOD CRI ≥ 90, traffic white

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
11.9 W, 1050 mA	2700 K	477 lm	40 lm/W	0 4 8 - 1 5 1 0 4 1 7 F
	3000 K	489 lm	41 lm/W	0 4 8 - 1 5 1 0 5 1 7 F



WIDE FLOOD CRI ≥ 90, traffic white

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
11.9 W, 1050 mA	2700 K	701 lm	59 lm/W	0 4 8 - 1 5 1 0 4 1 7 W
	3000 K	718 lm	61 lm/W	0 4 8 - 1 5 1 0 5 1 7 W



SPIO 60 adjustable



FLOOD CRI ≥ 90, traffic white


FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
11.9 W, 1050 mA	2700 K	455 lm	38 lm/W	0 4 8 - 1 5 2 0 4 1 7 F
	3000 K	466 lm	39 lm/W	0 4 8 - 1 5 2 0 5 1 7 F



WIDE FLOOD CRI ≥ 90, traffic white


FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
11.9 W, 1050 mA	2700 K	668 lm	56 lm/W	0 4 8 - 1 5 2 0 4 1 7 W
	3000 K	685 lm	58 lm/W	0 4 8 - 1 5 2 0 5 1 7 W

Mounting accessories (required)




MOUNTING SET trimless

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/25 mm	traffic white	73-29	0 4 8 - 2 6 9 6 1 1 7
for SASSO 60 round SPIO 60 downlight			




MOUNTING SET trimless adjustable

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/25 mm	traffic white	105-68	0 4 8 - 1 5 9 8 1 0 7
for SPIO 60 adjustable			



MOUNTING SET with trim adjustable for intermediate ceilings, 2-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	118-68	0 4 8 - 1 5 9 7 1 0 7
jet black	118-68	0 4 8 - 1 5 9 7 1 0 8
for SPIO 60 adjustable		



MOUNTING SET with trim downlight for intermediate ceilings, 2-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	81-39	0 4 8 - 1 5 9 7 2 0 7
jet black	81-39	0 4 8 - 1 5 9 7 2 0 8

for SPIO 60 downlight

Electrical accessories (required)

POWER SUPPLY

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
1050 mA 44 W PC2	176-264 V AC	η 89 %	143-43-30	0 0 2 - 9 0 7 8 8

Electrical accessories (optional)


DIN RAIL LED DRIVER



TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V

DIN RAIL POWER SUPPLY



L-W-H (mm)	ORDER CODE
72-90-63	0 0 5 - 6 5 2 0 2 1 0

220-240 V AC | 160W | 48V DC constant voltage

Accessories (required)

None

ORDER CODE
0 0 2 - 9 0 7 8 7

Calvin Klein, Paris

Francia

Architetto

Hyphen

Lighting Design

Mindseye Lighting

Fotografo

Miguel Jiménez



Prodotti utilizzati



SPIO 60 recessed



CAVO recessed



BO 55 / 70 track

