



## FRAME 40

recessed with trim


<sup>EN</sup> Luminaire housing made of extruded aluminium; recessed luminaire with trim; suitable for ceiling thickness of 8-25 mm; surface powder coated; luminaire profile can be pre-mounted; remaining luminaire components mounted without tools; light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

Il Corpo illuminante in profilo di alluminio estruso; apparecchio da incasso con bordo perimetrale; per soffitti di spessore 8-25 mm; verniciatura a polvere; profilo apparecchio pre-assemblabile; restanti componenti montabili senza utensili; unità d'illuminazione in profilo di alluminio estruso con verniciatura altamente riflettente per gestione termica migliorata; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
CRI  $\geq 90$ , 3 SDCM  
up to 116 lm/W  
L90 @ 50 000 h  
DALI-2  
opal

### Types

recessed trim 



### Colours



### Light distribution




opal




DiiA® standards  
251, 252, 253



system  
solution



tunable white  
2700–6500 K



CRI  $\geq 98$   
XPECTRUM

## Order options

COLOUR TEMPERATURE	
3000K	0
4000K	1

## CONTROL

DALI-2

## MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> white aluminium RAL 9006	G
<input type="radio"/> jet black RAL 9005	8

## LIGHT OPTIC COVER

opal high performance

## Options on request

## COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

## COLOUR TEMPERATURE

tunable white 2700–6500K



DALI-2 DT8

## LIGHT OPTIC COVER

microprismatic



## FRAME 40 trim



## MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
12.4W	3000K	1370lm	1019	0 4 2 - 7 1 1 2 :: 3 H
	4000K	1430lm		
24.8W	3000K	2730lm	2019	0 4 2 - 7 1 1 4 :: 3 H
	4000K	2860lm		
37W	3000K	4100lm	3019	0 4 2 - 7 1 1 6 :: 3 H
	4000K	4300lm		

## HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
20.1W	3000K	2140lm	1019	0 4 2 - 7 1 2 2 :: 3 H
	4000K	2240lm		
40W	3000K	4270lm	2019	0 4 2 - 7 1 2 4 :: 3 H
	4000K	4470lm		
60W	3000K	6410lm	3019	0 4 2 - 7 1 2 6 :: 3 H
	4000K	6710lm		

## Mounting accessories

## CONCRETE INSTALLATION HOUSING

L (mm)	W-H (mm)	ORDER CODE
1038	57-87	0 4 2 - 7 1 9 5 2 1 0
2038	57-87	0 4 2 - 7 1 9 5 4 1 0
3038	57-87	0 4 2 - 7 1 9 5 6 1 0

