



LENO

surface


^{EN} Low profile surface mounted luminaire, 28 mm total height; suitable for wall or ceiling mounting; surface powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering

^{IT} Apparecchio a plafone ultrapiatto da 28 mm di altezza totale; per montaggio a parete o soffitto; verniciatura a polvere; inserto luce anti-caduta in profilo di alluminio estruso, fissaggio nel canale con magnete senza bisogno di utensili; luce convogliata lateralmente e direzionata in basso con sistema LGP-Body (Light Guiding Prism) e riflettore ad alta efficienza; diffusore satinato (a filo o sporgente) o con struttura a microprismi a illuminazione omogenea in PMMA; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
UGR $\leq$ 19
fino a 2,130 lm/m
fino a 137 lm/W
L90 / 50000 h
DALI-2
High Performance Opal, Jut-Out, Microprismatic
IP20

Types



Colore




Distribuzione della luce



DiiA® standards
251, 252, 253




system solution



microprismatic
UGR $\leq$ 19



quick
installation



LENOR surface



MICROPRISMATIC DALI-2, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	618 mm	3000 K	1160 lm	107 lm/W	0 5 1 - 9 1 1 2 5 3 G
		4000 K	1230 lm	114 lm/W	0 5 1 - 9 1 1 2 6 3 G
19.1 W	1226 mm	3000 K	2320 lm	121 lm/W	0 5 1 - 9 1 1 4 5 3 G
		4000 K	2450 lm	128 lm/W	0 5 1 - 9 1 1 4 6 3 G
28.6 W	1835 mm	3000 K	3480 lm	122 lm/W	0 5 1 - 9 1 1 6 5 3 G
		4000 K	3680 lm	129 lm/W	0 5 1 - 9 1 1 6 6 3 G
38.0 W	2443 mm	3000 K	4630 lm	122 lm/W	0 5 1 - 9 1 1 8 5 3 G
		4000 K	4910 lm	129 lm/W	0 5 1 - 9 1 1 8 6 3 G



OPAL DALI-2, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	618 mm	3000 K	1220 lm	113 lm/W	0 5 1 - 9 1 1 2 5 3 H
		4000 K	1300 lm	120 lm/W	0 5 1 - 9 1 1 2 6 3 H
19.1 W	1226 mm	3000 K	2450 lm	128 lm/W	0 5 1 - 9 1 1 4 5 3 H
		4000 K	2590 lm	136 lm/W	0 5 1 - 9 1 1 4 6 3 H
28.6 W	1835 mm	3000 K	3670 lm	128 lm/W	0 5 1 - 9 1 1 6 5 3 H
		4000 K	3890 lm	136 lm/W	0 5 1 - 9 1 1 6 6 3 H
38.0 W	2443 mm	3000 K	4900 lm	129 lm/W	0 5 1 - 9 1 1 8 5 3 H
		4000 K	5190 lm	137 lm/W	0 5 1 - 9 1 1 8 6 3 H

OPAL JUT-OUT DALI-2, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	618 mm	3000 K	1170 lm	108 lm/W	0 5 1 - 9 1 1 2 5 3 J
		4000 K	1240 lm	115 lm/W	0 5 1 - 9 1 1 2 6 3 J
19.1 W	1226 mm	3000 K	2350 lm	123 lm/W	0 5 1 - 9 1 1 4 5 3 J
		4000 K	2490 lm	130 lm/W	0 5 1 - 9 1 1 4 6 3 J
28.6 W	1835 mm	3000 K	3520 lm	123 lm/W	0 5 1 - 9 1 1 6 5 3 J
		4000 K	3730 lm	130 lm/W	0 5 1 - 9 1 1 6 6 3 J
38.0 W	2443 mm	3000 K	4700 lm	124 lm/W	0 5 1 - 9 1 1 8 5 3 J
		4000 K	4970 lm	131 lm/W	0 5 1 - 9 1 1 8 6 3 J

Planning Information



LENOR surface, microprismatic,
19.1W, 4000K

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Order options

COLOUR

pure white RAL 9010	7
jet black RAL 9005	8