

MITA circle 240 / 450

recessed


EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante circolare in alluminio pressofuso; forma estremamente sottile; apparecchio da incasso con bordo perimetrale; in opzione: copertura cieca per l'inserimento nel vano interno disponibile come accessorio; per soffitti di spessore 2-25 mm; verniciatura a polvere; riflettore ad alta lucentezza con design sfaccettato; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K, tunable white
2700 K - 6500 K
CRI $\geq$ 80, CRI $\geq$ 90 / 3 SDCM
UGR $\leq$ 16, UGR $\leq$ 19
fino a 161 lm/W
L90 / 50000 h
DALI-2
Reflector
IP20

Types



Colore



Riflettore




Distribuzione della luce




suitable for
plasterboard or
grid ceilings



DIN EN 12464-1
UGR $\leq$ 19



tunable white
2700 - 6500 K



MITA circle 240 trim

TUNABLE
WHITECRI
≥ 90UGR
≤ 16cd/m²
≤ 1500

220-240 V



DALI
1ADDR.

X-PERT

X-PERT

REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	REFLECTOR	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
13.8 W	3000 K	chrome	80	1950 lm	141 lm/W	0 7 4 - 8 1 1 4 5 3 ☒ R
			90	1680 lm	122 lm/W	0 7 4 - 8 1 1 4 0 3 ☒ R
		dark chr.	80	1400 lm	101 lm/W	0 7 4 - 8 1 1 4 5 3 ☒ B
			90	1200 lm	87 lm/W	0 7 4 - 8 1 1 4 0 3 ☒ B
	4000 K	chrome	80	2220 lm	161 lm/W	0 7 4 - 8 1 1 4 6 3 ☒ R
			90	1810 lm	131 lm/W	0 7 4 - 8 1 1 4 1 3 ☒ R
		dark chr.	80	1590 lm	115 lm/W	0 7 4 - 8 1 1 4 6 3 ☒ B
			90	1300 lm	94 lm/W	0 7 4 - 8 1 1 4 1 3 ☒ B
14.2 W	tunable w.	chrome	90	1670 lm	118 lm/W	0 7 4 - 8 1 1 4 D 3 ☒ R
		dark chr.	90	1200 lm	85 lm/W	0 7 4 - 8 1 1 4 D 3 ☒ B



MITA circle 450 trim

TUNABLE
WHITECRI
≥ 90UGR
≤ 19cd/m²
≤ 1500

220-240 V


DALI
1ADDR.

X-PERT

X-PERT

REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	REFLECTOR	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
28.5 W	tunable w.	chrome	90	3340 lm	117 lm/W	0 7 4 - 8 1 1 6 D 3 ☒ R
		dark chr.	90	2390 lm	84 lm/W	0 7 4 - 8 1 1 6 D 3 ☒ B
30.0 W	3000 K	chrome	80	4210 lm	140 lm/W	0 7 4 - 8 1 1 6 5 3 ☒ R
			90	3630 lm	121 lm/W	0 7 4 - 8 1 1 6 0 3 ☒ R
		dark chr.	80	3010 lm	100 lm/W	0 7 4 - 8 1 1 6 5 3 ☒ B
			90	2600 lm	87 lm/W	0 7 4 - 8 1 1 6 0 3 ☒ B
	4000 K	chrome	80	4790 lm	160 lm/W	0 7 4 - 8 1 1 6 6 3 ☒ R
			90	3920 lm	131 lm/W	0 7 4 - 8 1 1 6 1 3 ☒ R
		dark chr.	80	3430 lm	114 lm/W	0 7 4 - 8 1 1 6 6 3 ☒ B
			90	2800 lm	93 lm/W	0 7 4 - 8 1 1 6 1 3 ☒ B
40.0 W	3000 K	chrome	80	5470 lm	137 lm/W	0 7 4 - 8 1 2 6 5 3 ☒ R
			90	4720 lm	118 lm/W	0 7 4 - 8 1 2 6 0 3 ☒ R
		dark chr.	80	3920 lm	98 lm/W	0 7 4 - 8 1 2 6 5 3 ☒ B
			90	3380 lm	85 lm/W	0 7 4 - 8 1 2 6 0 3 ☒ B
	4000 K	chrome	80	6230 lm	156 lm/W	0 7 4 - 8 1 2 6 6 3 ☒ R
			90	5100 lm	128 lm/W	0 7 4 - 8 1 2 6 1 3 ☒ R
		dark chr.	80	4460 lm	112 lm/W	0 7 4 - 8 1 2 6 6 3 ☒ B
			90	3650 lm	91 lm/W	0 7 4 - 8 1 2 6 1 3 ☒ B



Optical accessories (optional)

BLIND COVER circle 240

COLOUR

traffic white

jet black

ORDER CODE

0 7 4 - 8 9 1 1 4 1 7

0 7 4 - 8 9 1 1 4 1 8

BLIND COVER circle 450

COLOUR

traffic white

jet black

ORDER CODE

0 7 4 - 8 9 1 1 6 1 7

0 7 4 - 8 9 1 1 6 1 8

Order options

COLOUR

traffic white RAL 9016

jet black RAL 9005



7

8

Endress+Hauser GmbH, Vienna

Austria

Architetto

FOKURA Luxury
Interior, Reinhard
Strempl

Lighting Design

Ing. Gerhard Heil, TB Heil
& Schafzahl GmbH

Fotografo


Kurt Kuball



Prodotti utilizzati



SONIC suspended



MITA circle 240 /
450 recessed



UNICO L4 / L6 basic
recessed



