



BO 32 / 45 / 55

intrack

EN Track light made of die-cast aluminium; powder coated; spotlight head rotates 360° and tilts 90°; choice of single lamp, double lamps or triple lamp; converter in the adapter; with optional high quality lens system with precise radiation characteristic; or high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; good glare reduction due to recessed light point plane; optical attachments as accessories; COB (Chip on Board) technology or high power LEDs - maximum efficiency; no multiple shadows; energy-eff. LEDs - very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter flush with the power track

IT Faretto da binario elettrificato in alluminio pressofuso; verniciatura a polvere; testata ruotabile di 360° e orientabile di 90°; con una, due o tre luci a scelta; convertitore nell'adattatore; a scelta con ottica lenticolare di precisione; oppure riflettore d'alta qualità con ottica sfaccettata in alluminio applicato a vapore; curva fotometrica precisa con diversi angoli di emissione; ottima schermatura con superficie di emissione arretrata; unità ottiche come accessori; tecnologia COB (Chip on Board) o LED high power - massima efficienza; assenza di ombre multiple; LED a risp. energ. - ottima resa cromatica; adattatore per installazione senza utensili o scorrimento in vari binari trifase; adattatore a filo con i binari elettrificati

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90, 2 SDCM
 BO 32 up to 87lm/W
 BO 45 up to 91lm/W
 BO 55 up to 84lm/W
 L85 @ 50000 h
 DALI-2


Types



Colours



Light distributions



only one adapter with 2 or 3 lamps



360° rotatable 90° tiltable



glare control via honeycomb louver



oval lens for oval light illumination



CRI ≥ 90 2 SDCM

Order options

COLOUR TEMPERATURE

| | |
|-------|---|
| 2700K | 4 |
| 3000K | 5 |
| 3500K | 7 |
| 4000K | 6 |

CONTROL

DALI-2

MATERIAL COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

BEAM ANGLE BO 32

| | |
|------------|---|
| spot 18° | S |
| medium 23° | M |
| flood 37° | F |






BEAM ANGLE BO 45

| | |
|---------------|---|
| super spot 8° | V |
| spot 14° | S |
| medium 24° | M |
| flood 39° | F |

BEAM ANGLE BO 55

| | |
|------------|---|
| spot 17° | S |
| medium 31° | M |
| flood 37° | F |

LUMINOUS FLUX value calculated for
3000K, CRI ≥ 90, colour white, flood
2700K -5%, 3500K +0.5%, 4000K +7%



BO 32 intrack



TRACK LIGHT

| TYPE | SYS. POWER | LUMINOUS FLUX | ORDER CODE |
|---------|------------|---------------|--------------|
| 1 lamp | 10.7W | 755lm | 180-7130::3▲ |
| 2 lamps | 20.5W | 1440lm | 180-7140::3▲ |
| 3 lamps | 32.0W | 2380lm | 180-7150::3▲ |

BO 45 intrack



TRACK LIGHT

| TYPE | SYS. POWER | LUMINOUS FLUX | ORDER CODE |
|---------|------------|----------------------|---------------|
| 1 lamp | 8.5W* | super spot 346lm | 180-7230::3▲V |
| | 15.1W | spot 1120lm | 180-7230::3▲S |
| 2 lamps | 15.9W | medium, flood 1320lm | 180-7230::3▲M |
| | 14.2W* | super spot 2×320lm | 180-7240::3▲V |
| 3 lamps | 30W | spot 2×1020lm | 180-7240::3▲S |
| | 32W | med., flood 2×1330lm | 180-7240::3▲M |
| | 45W | spot 3×1020lm | 180-7250::3▲S |
| | 42W | med., flood 3×1180lm | 180-7250::3▲M |

*do not use optical filters

BO 55 intrack



TRACK LIGHT

| TYPE | SYS. POWER | LUMINOUS FLUX | ORDER CODE |
|---------|------------|---------------|--------------|
| 1 lamp | 24.8W | 1940lm | 180-7330::3▲ |
| 2 lamps | 43W | 3460lm | 180-7340::3▲ |

Optical accessories

HONEYCOMB LOUVER

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 32 | 30·3 | 007-1965168 |
| BO 45 | 42·3 | 007-1965188 |
| BO 55 | 50·3 | 007-1965598 |

OVAL LENS

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 32 | 30·3 | 007-1965860 |
| BO 45 | 42·3 | 007-1965880 |
| BO 55 | 50·3 | 007-1965890 |

SOFT LENS

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 32 | 30·3 | 007-1965960 |
| BO 45 | 42·3 | 007-1965980 |
| BO 55 | 50·3 | 007-1965990 |

WALLWASHER LENS

| TYPE | Ø-H (mm) | ORDER CODE |
|-------|----------|-------------|
| BO 32 | 30·3 | 007-1965760 |
| BO 45 | 42·3 | 007-1965780 |
| BO 55 | 50·3 | 007-1965790 |



Types



Colours



TRACK 3-phase
recessed/surface/suspended



TRACK recessed

Order options

CONTROL

non DIM



DALI-2

MATERIAL COLOUR

○ pure white RAL 9010 7

● jet black RAL 9005 8

Pole options



TRACK 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

| L (mm) | ORDER CODE |
|--------|------------|
| 2000 | 186-012213 |
| 3000 | 186-012313 |
| 4000 | 186-012413 |

end cap 186-022011

end feed left 186-022313
 end feed right 186-022413
 middle feed 186-021323

CONNECTORS 240V-16A

TYPE ORDER CODE
 linear connector 186-021113

I-connector 186-022123

L-connector right 186-022133
 L-connector left 186-022233

T-connector right (poles internal) 186-022143
 T-connector left (poles internal) 186-022243
 T-connector right (poles external) 186-022173
 T-connector left (poles external) 186-022273






X-connector 186-022153

MOUNTING ACCESSORIES

TYPE ORDER CODE
 clip 186-0225110

cutting tool 186-0219110

35xL



TRACK

surface/suspended

Order options

CONTROL

non DIM
DALI-2

MATERIAL COLOUR

- pure white RAL 9010 7
- grey 6
- jet black RAL 9005 8

Pole options



TRACK 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

| L (mm) | ORDER CODE |
|--------|------------|
| 1000 | 186-011123 |
| 2000 | 186-011223 |
| 3000 | 186-011323 |
| 4000 | 186-011423 |

end cap 186-021011

end feed left 186-021313
end feed right 186-021413
middle feed* 186-021323

*only available in white and black

CONNECTORS 240V-16A

TYPE ORDER CODE
linear connector 186-021113

I-connector 186-021123

L-connector right 186-021133

L-connector left 186-021233

T-connector right (poles internal) 186-021143

T-connector left (poles internal) 186-021243

T-connector right (poles external) 186-021173

T-connector left (poles external) 186-021273

X-connector 186-021153

adjustable corner connector 186-021163

MOUNTING ACCESSORIES

TYPE ORDER CODE
ceiling clip 186-021511

pendant clip cable 186-021521

pendant clip rod 186-021541

joiner piece cable 186-021531

joiner piece rod 186-021551

cutting tool 186-0219110

SUSPENSION KIT

TYPE ORDER CODE
pendant 1000 186-021611

cable 1500 186-0217110

cable 3000 186-0217210

cable 5000 186-0217310



TRACK high

surface/suspended

Order options

CONTROL

non DIM

DALI-2

MATERIAL COLOUR

○ pure white RAL 9010 7

● jet black RAL 9005 8

Options on request

LIGHT OPTIC COVER

inset indirect


Pole options




poles internal left



poles internal right



poles external left



poles external right



poles end feed left



poles end feed right

TRACK high 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

| L (mm) | ORDER CODE |
|--------|------------|
| 1000 | 186-016113 |
| 2000 | 186-016213 |
| 3000 | 186-016313 |
| 4000 | 186-016413 |

end cap 186-026011

end feed left 186-026313

end feed right 186-026413

middle feed 186-021323

CONNECTORS 240V-16A

TYPE
linear connector 186-026113

I-connector 186-026123

L-connector right 186-026133

L-connector left 186-026233

T-connector right (poles internal) 186-026143

T-connector left (poles internal) 186-026243

T-connector right (poles external) 186-026173

T-connector left (poles external) 186-026273

X-connector 186-026153

MOUNTING ACCESSORIES

TYPE
pendant clip cable 186-0265210
pendant sheet metal clip 186-0215220
pendant clip rod 186-0265410

joiner piece cable 186-0265310

joiner piece rod 186-0265510

cutting tool 186-0219110

SUSPENSION KIT

TYPE
pendant 1000 186-0216110

cable 1500 186-0217110

cable 3000 186-0217210

cable 5000 186-0217310



TRACK round surface/suspended

Order options

CONTROL


non DIM

DALI-2

MATERIAL COLOUR

- pure white RAL 9010 7
- jet black RAL 9005 8

Pole options



TRACK round 3-phase/3-phase + DALI-2-bus



TRACK 240V-16A

| L (mm) | ORDER CODE |
|--------|------------|
| 1000 | 186-015113 |
| 2000 | 186-015213 |
| 3000 | 186-015313 |
| 4000 | 186-015413 |



TRACK CURVE 240V-16A

| TYPE | ORDER CODE |
|-----------------|------------|
| R 500 90° left | 186-015853 |
| R 500 90° right | 186-015863 |



end cap 186-025011



end feed left 186-025313
 end feed right 186-025413
 middle feed 186-021323



CONNECTORS 240V-16A

linear connector 186-021113



L-connector right (external) 186-025133
 L-connector left (internal) 186-025233

T-connector left (poles external) 186-025243
 T-connector right (poles external) 186-025143
 T-connector right (poles internal) 186-025273
 T-connector left (poles internal) 186-025173



X-connector 186-025153

MOUNTING ACCESSORIES

pendant clip cable 186-025521
 pendant clip rod 186-025541

joiner piece cable 186-025531
 joiner piece rod 186-025551

cutting tool 186-0279110

SUSPENSION KIT

pendant 1000 186-021611

cable 1500 186-0217110
 cable 3000 186-0217210
 cable 5000 186-0217310