



MITA circle

suspended

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct/indirect light distribution; energy-efficient LEDs with very good colour rendering


IT Corpo illuminante circolare in alluminio pressofuso; forma estremamente sottile; verniciatura a polvere; sospeso; con asta di sospensione accorciabile (cromata), cavo alimentazione nell'asta di sospensione; alimentatore elettronico montato nel rosone; in opzione: copertura cieca, fissata nel vano interno per mezzo di un magnete, disponibile come accessorio; riflettore ad alta lucentezza con design sfaccettato; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; a scelta con emissione diretta oppure diretta/indiretta; LED ad efficienza energetica con elevata resa cromatica

Quickinfo


3000 K, 4000 K
 CRI \geq 80, 3 SDCM
 UGR \leq 19 / $65^\circ \leq 1500$ cd/m²
 up to 160 lm/W
 L90 @ 50 000h
 DALI-2, DALI-2 sensor
 reflector (UGR \leq 19), opal

Types

suspended



Colours



Light distributions



dark chrome
reflector option




up to 160 lm/W
(high efficiency)



sensor version
available



version with
opal cover



magnetic
blind cover



DIN EN 12464-1
UGR \leq 19

Order options

SUSPENSION

rod 1000 mm

COLOUR TEMPERATURE

3000K	5
4000K	6

CONTROL

DALI-2	3
DALI-2 ESSENTIAL sensor (brightness & presence)	B
DALI-2 SENSE sensor (brightness, presence, temp., sound pressure, humidity, CO ₂)	P

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR COLOUR

↗ chrome	R
● dark chrome	B

LIGHT OPTIC COVER

reflector (UGR ≤ 19)
opal

Options on request

SUSPENSION



rod 1000 mm white
rod 1000 mm black

COLOUR RENDERING INDEX

CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700–6500K



MITA circle 450 suspended



UGR
≤ 19

cd/m²
≤ 1500

DALI
1ADDR.

220-240V

X-PERT

X-PERT

REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30W	3000K	4210lm	074-76111
	4000K	4790lm	
41W	3000K	5470lm	074-76211
	4000K	6230lm	

OPAL DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
25.1W	3000K	2770lm	074-76111
	4000K	3060lm	



UGR
≤ 19

cd/m²
≤ 1500

DALI
1ADDR.

220-240V

X-PERT

X-PERT

REFLECTOR DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
58W	3000K	↓ 4030 / ↑ 3780lm	074-76511
	4000K	↓ 4600 / ↑ 4310lm	

OPAL DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
58W	3000K	↓ 3140 / ↑ 3780lm	074-76511
	4000K	↓ 3570 / ↑ 4310lm	

Accessories

BLIND COVER

TYPE	ORDER CODE
MITA circle 450 suspended	074-891162
MITA circle 450 suspended sensor	074-891163