



MINO CIRCLE S

suspended

EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; flat design luminaire housing; surface powder coated; pendant fitting with cable suspension, alternatively with canopy central; height adjustment without tools; incl. feed (black or white); converter included in canopy; HPO (High Performance Opal) cover for uniform illumination; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering


IT Corpo illuminante circolare in profilo di alluminio estruso rollato e senza punti di saldatura; forma piatta; verniciatura a polvere; sospeso con cavo a sospensione, a scelta con rosone centrale; regolazione altezza senza utensili; incl. cavo di alimentazione (nero o bianco); convertitore integrato nel rosone; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; in opzione con emissione diretta/indiretta per ulteriore accentuazione del soffitto e migliore comfort visivo; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 121 lm/W
L90 @ 50 000 h
DALI-2
opal


Types

suspended



ø 1060 ø 1560

Luminaire colours



Light distributions



direct direct
indirect



direct/indirect
illumination



DiiA® standards
251, 252, 253

Order options

SUSPENSION	
cable 1500 mm	2
cable 1500 mm/canopy central	4

COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL


DALI-2

for direct/indirect version:
separately controllable (direct
and indirect part)

LUMINAIRE COLOUR	
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours	X

LIGHT OPTIC COVER

opal high performance



*canopy direct/indirect version

MINO 60 CIRCLE S 1000 suspended




DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
70 W	3000K	7070lm	0 3 4 - 7 5 1 2 :: 3 H
	4000K	7340lm	



DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
90 W	3000K	↓ 7070 / ↑ 3420 lm	0 3 4 - 7 5 1 3 :: 3 H
	4000K	↓ 7350 / ↑ 3550 lm	



*canopy direct/indirect version

MINO 60 CIRCLE S 1500 suspended



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
96 W	3000K	9980lm	0 3 4 - 7 5 1 0 :: 3 H
	4000K	10400lm	



DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
136 W	3000K	↓ 9980 / ↑ 5290 lm	0 3 4 - 7 5 1 1 :: 3 H
	4000K	↓ 10400 / ↑ 5610 lm	

Light distribution



opal
direct/indirect

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, cover opal