



## STADIO 10

semi-recessed

**EN** Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered; spotlight head rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

**IT** Faretto miniaturizzato cilindrico in alluminio con montaggio a semincasso; verniciatura; testa del faretto ruotabile e orientabile; ottica lenticolare di qualità; curva fotometrica precisa con diversi angoli di emissione; LED ad efficienza energetica con elevata resa cromatica; montaggio senza attrezzi tramite connettore con innesto rapido a baionetta; convertitore premon-tato e pronto all'uso; convertitore da ordinare separatamente

### Quickinfo

3000 K, 4000 K  
CRI  $\geq 95$  / 3 SDCM  
fino a 106 lm/W  
L80 / 50000 h, L85 / 50000 h  
excl. driver  
IP20

### Types



### Colore



### Distribuzione della luce



CRI  $\geq 95$ , R9  $\geq 90$



360° rotatable,  
90° tiltable



plug & play



## STADIO 10 semi-recessed



### SPOT excl. driver, CRI ≥ 95

| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE | ORDER CODE  |
|---------------|--------------|-----------|---------|---|
| 0.6 W, 220 mA | 3000 K       | 44 lm     | 71 lm/W | 0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> S |
|               | 4000 K       | 44 lm     | 69 lm/W | 0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> S |

light inset incl. connection cable with socket 0.5m

### MEDIUM excl. driver, CRI ≥ 95


| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE  | ORDER CODE  |
|---------------|--------------|-----------|----------|---|
| 0.6 W, 220 mA | 3000 K       | 60 lm     | 104 lm/W | 0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> M |
|               | 4000 K       | 65 lm     | 105 lm/W | 0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> M |

light inset incl. connection cable with socket 0.5m

### FLOOD excl. driver, CRI ≥ 95

| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE  | ORDER CODE  |
|---------------|--------------|-----------|----------|---|
| 0.6 W, 220 mA | 3000 K       | 60 lm     | 105 lm/W | 0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> F |
|               | 4000 K       | 66 lm     | 106 lm/W | 0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> F |

light inset incl. connection cable with socket 0.5m



## Electrical accessories (optional)

### POWER SUPPLY EU 220 mA

| TYPE    | L-W-H (mm) | ORDER CODE            |
|---------|------------|-----------------------|
| DALI-2  | 145-33-21  | 0 1 1 - 9 2 1 1 1 3 0 |
| non DIM | 115-19-34  | 0 1 1 - 9 2 1 1 2 1 0 |

incl. power cable 2m + connection cable with plug 1m

### POWER SUPPLY UL 220 mA

| TYPE         | L-W-H (mm) | ORDER CODE            |
|--------------|------------|-----------------------|
| non DIM      | 115-19-34  | 0 1 1 - 9 2 8 1 2 1 0 |
| DALI-2/0-10V | 111-22-52  | 0 1 1 - 9 2 8 1 3 2 0 |

incl. connection cable with plug 1m

### EXTENSION CABLE 1 × socket / 1 × plug

| FEEDER LENGTH | ORDER CODE            |
|---------------|-----------------------|
| 1000 mm       | 0 1 1 - 9 2 2 1 1 2 0 |
| 2000 mm       | 0 1 1 - 9 2 2 1 1 4 0 |
| 4000 mm       | 0 1 1 - 9 2 2 1 1 8 0 |

### SPLITTER SERIAL

| TYPE                  | L-W-H (mm) | ORDER CODE            |
|-----------------------|------------|-----------------------|
| 3 × socket / 1 × plug | 38-30-10   | 0 1 1 - 9 2 2 8 3 0 0 |
| 6 × socket / 1 × plug | 55-32-10   | 0 1 1 - 9 2 2 8 6 0 0 |

## Order options

| COLOUR                   |                                       |
|--------------------------|---------------------------------------|
| white aluminium RAL 9006 | <input checked="" type="checkbox"/> 6 |
| tar black RAL 9021       | 8                                     |