



## STADIO 10

semi-recessed

**EN** Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered; spotlight head rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

**IT** Faretto miniaturizzato cilindrico in alluminio con montaggio a semincasso; verniciatura; testa del faretto ruotabile e orientabile; ottica lenticolare di qualità; curva fotometrica precisa con diversi angoli di emissione; LED ad efficienza energetica con elevata resa cromatica; montaggio senza attrezzi tramite connettore con innesto rapido a baionetta; convertitore premon-tato e pronto all'uso; convertitore da ordinare separatamente

### Quickinfo

3000 K, 4000 K  
CRI  $\geq 95$  / 3 SDCM  
fino a 106 lm/W  
L80 / 50000 h, L85 / 50000 h  
excl. driver  
IP20

### Types



### Colore



### Distribuzione della luce



CRI  $\geq 95$ , R9  $\geq 90$



360° rotatable,  
90° tiltable



plug & play



## STADIO 10 semi-recessed



### SPOT excl. driver, CRI ≥ 95

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
0.6 W, 220 mA	3000 K	44 lm	71 lm/W	0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> S
	4000 K	44 lm	69 lm/W	0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> S

light inset incl. connection cable with socket 0.5m

### MEDIUM excl. driver, CRI ≥ 95


FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
0.6 W, 220 mA	3000 K	60 lm	104 lm/W	0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> M
	4000 K	65 lm	105 lm/W	0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> M

light inset incl. connection cable with socket 0.5m

### FLOOD excl. driver, CRI ≥ 95

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
0.6 W, 220 mA	3000 K	60 lm	105 lm/W	0 1 1 - 8 0 0 0 0 1 <input checked="" type="checkbox"/> F
	4000 K	66 lm	106 lm/W	0 1 1 - 8 0 0 0 1 1 <input checked="" type="checkbox"/> F

light inset incl. connection cable with socket 0.5m



## Electrical accessories (optional)

### POWER SUPPLY EU 220 mA

TYPE	L-W-H (mm)	ORDER CODE
DALI-2	145-33-21	0 1 1 - 9 2 1 1 1 3 0
non DIM	115-19-34	0 1 1 - 9 2 1 1 2 1 0

incl. power cable 2m + connection cable with plug 1m

### POWER SUPPLY UL 220 mA

TYPE	L-W-H (mm)	ORDER CODE
non DIM	115-19-34	0 1 1 - 9 2 8 1 2 1 0
DALI-2/0-10V	111-22-52	0 1 1 - 9 2 8 1 3 2 0

incl. connection cable with plug 1m

### EXTENSION CABLE 1 × socket / 1 × plug

FEEDER LENGTH	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 1 2 0
2000 mm	0 1 1 - 9 2 2 1 1 4 0
4000 mm	0 1 1 - 9 2 2 1 1 8 0

### SPLITTER SERIAL

TYPE	L-W-H (mm)	ORDER CODE
3 × socket / 1 × plug	38-30-10	0 1 1 - 9 2 2 8 3 0 0
6 × socket / 1 × plug	55-32-10	0 1 1 - 9 2 2 8 6 0 0

## Order options

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> 6
tar black RAL 9021	8