

# MINO 60 high lumen

ceiling / suspended system

007-93M5537 006-16152H 046-400501X



Progetto / Tipo \_\_\_\_\_

Appunti \_\_\_\_\_

Quantità / Data \_\_\_\_\_



## Generale

Soffitto , Sospeso \_\_\_\_\_

colori speciali \_\_\_\_\_

2350 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

3460 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI  $\geq 80$  \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

sicurezza fotobio. RG 0 - Rischio esente \_\_\_\_\_

MacAdam iniziale  $\leq 3$  SDCM \_\_\_\_\_

MR 0.56 \_\_\_\_\_

MDER 0.51 \_\_\_\_\_

## Ottico

High Performance Opal \_\_\_\_\_

PstLM  $\leq 1.0$  <sup>1</sup> \_\_\_\_\_

SVM  $\leq 0.4$  <sup>1</sup> \_\_\_\_\_

## Dati elettrici

DALI-2 \_\_\_\_\_

29.1 W \_\_\_\_\_

classe isolamento 1 220-240V \_\_\_\_\_

119 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

20 W/m \_\_\_\_\_

## Dati fisici

bordo \_\_\_\_\_

lunghezza 1472 mm \_\_\_\_\_

larghezza 60 mm \_\_\_\_\_

altezza 80 mm \_\_\_\_\_

3.6 kg \_\_\_\_\_

<sup>1</sup> Valore del prodotto contenitore a pieno carico (non regolato)

## Distribuzione della luce



## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

