



SASSO 40 round

recessed

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

IT Faretto a incasso rotondo; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura; incasso possibile in vari telai; a scelta orientabile / fisso simmetrico o asimmetrico caratteristiche di emissione; varianti con emissione simmetrica: emissione precisa con ottica lenticolare di alta qualità; varianti a fascio asimmetrica: riflettore di alta qualità con superficie a microfacette e vaporizzata in alluminio; tecnologia COB (Chip on Board) per la massima efficienza (ADJUSTABLE e DOWNLIGHT); assenza di ombre multiple; LED efficienti con alta resa cromatica

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 117 lm/W
L80 @ 50000 h
non DIM, DALI-2
↓ IP44/↑ IP20

Types

trim	 50-55
	ø 60
trimless	 50-55
	ø 45
double trim	 50-55
	120x60

Housing colours



Inset colours



Light distributions



rotatable 360°,
tiltable 30°



wallwasher and
ww floor inset



glare control
(UGR ≤ 16)

Order options

COLOUR TEMPERATURE ADJUSTABLE / DOWNLIGHT ⬢

2700 K	4
3000 K	5
4000 K	6

COLOUR TEMPERATURE WALLWASHER / WW FLOOR ⬢

2700 K	9
3000 K	0
3500 K	2
4000 K	1

INSET COLOUR ⬢





<input type="radio"/> traffic white RAL 9016 (UGR _{≤22})	7
<input type="radio"/> matt silver (UGR _{≤19})	4
<input type="radio"/> jet black RAL 9005 (UGR _{≤16})	1
<input type="radio"/> gold dust RAL 260-M (UGR _{≤19})	9

BEAM ANGLE ▲

spot 14°	S
medium 27°	M
flood 45°	F

Options on request

POWER SUPPLY
DIM 1–10 V



Light distributions



wallwasher

wallwasher floor

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, medium 2700 K -5%, 4000 K +5%



SASSO 40 round



ADJUSTABLE (↓ IP 40 | ↑ IP 20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
5.1 W 12 Vf 450 mA	417 lm	0 4 8 - 2 8 2 0 ⬢ 1 ▲

DOWNLIGHT (↓ IP 44 | ↑ IP 20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
5.1 W 12 Vf 450 mA	415 lm	0 4 8 - 2 8 0 0 ⬢ 1 ▲



WALLWASHER (IP 20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
6.3 W 36 Vf 200 mA	484 lm	0 4 8 - 2 8 4 0 ⬢ 1 ▲

WALLWASHER / FLOOR (IP 20)

INSET POWER	LUMINOUS FLUX	ORDER CODE
6.9 W 27 Vf 200 mA	812 lm	0 4 8 - 2 8 4 0 ⬢ 1 ▲

Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

COLOUR	ORDER CODE
<input type="radio"/> traffic white RAL9016	0 4 8 - 2 8 9 6 1 1 7

MOUNTING SET WITH TRIM for intermediate ceilings 2–25 mm

TYPE	COLOUR	ORDER CODE
1 lamp	<input type="radio"/> traffic white RAL9016	0 4 8 - 2 8 9 6 3 1 7
	<input checked="" type="radio"/> jet black RAL 9005	0 4 8 - 2 8 9 6 3 1 8
2 lamps	<input type="radio"/> traffic white RAL9016	0 4 8 - 2 8 9 8 3 1 7
	<input checked="" type="radio"/> jet black RAL 9005	0 4 8 - 2 8 9 8 3 1 8

TRIMLESS MOUNTING SET for soft acoustic ceilings 25–40 mm

COLOUR	ORDER CODE
<input type="radio"/> signal white RAL 9003	0 4 8 - 2 8 9 6 1 9 7

MOUNTING SET WITH TRIM for soft acoustic ceilings 25–40 mm

TYPE	COLOUR	ORDER CODE
1 lamp	<input type="radio"/> signal white RAL 9003	0 4 8 - 2 8 9 6 3 9 7
	<input checked="" type="radio"/> traffic black RAL 9017	0 4 8 - 2 8 9 6 3 9 8

MOUNTING TOOL for soft acoustic ceilings

TYPE	COLOUR	ORDER CODE
SASSO 40	<input checked="" type="radio"/> traffic black RAL 9017	0 4 8 - 2 8 9 5 9 1 8

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
200 mA non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 4
200 mA DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 0
450 mA non DIM	η 88 %	138-30-21	0 0 2 - 9 0 7 5 2
450 mA DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 5 3

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
200 mA non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 4
200 mA DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 0
450 mA non DIM	η 88 %	138-30-21	0 0 2 - 9 0 7 5 2
450 mA DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 5 3

POWER SUPPLY w. loop through function 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
200 mA DALI-2	η 87 %	185-30-21	0 0 2 - 9 0 7 4 9
450 mA DALI-2	η 87 %	185-30-21	0 0 2 - 9 0 7 5 0

POWER SUPPLY PRE-WIRED

with loop through function 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	ORDER CODE
200 mA DALI-2	η 87 %	0 0 2 - 9 0 7 4 9 A

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W 48 V DC constant voltage	72-90-63	0 0 5 - 6 5 2 0 2 1 0
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2 x 42 W 48 V DC U _{OUT} 10-40 V	36-88-59	0 0 5 - 6 1 2 1 0 3 0

for more details and components see catalog XAL 22, page 981