



INO TRIPLE circle

suspended

EN 3 pcs. ring-shaped light fittings in rolled and seamlessly welded extruded aluminium profile; surface powder coated; pendant fitting with cable suspension; height adjustment without tools; light fitting individually height adjustable; incl. transparent feed; 3 pcs. electronic operating units installed in the canopy; completely homogeneously illuminated, satinised PMMA cover; inwards facing emission characteristics; direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; canopy with 2 cable openings and plug-in terminal for through wiring

IT 3 corpi illuminanti circolari in profilo di alluminio estruso laminato e saldato senza interruzioni; verniciatura a polvere; sospeso con cavo a sospensione; regolazione altezza senza utensili; corpo faro ad anello regolabile in altezza individualmente; incl. cavo di alimentazione trasparente; 3 alimentatori elettronici inseriti nel rosone; diffusore satinato in PMMA a illuminazione assolutamente omogenea; emissione verso l'interno; emissione diretta/indiretta per maggiore accentuazione del soffitto e migliore comfort visivo; LED ad efficienza energetica con elevata resa cromatica; rosone con 2 ingressi cavi e morsetto per cablaggio passante

Quickinfo

2700 K, 3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM
L90 / 50000 h
DALI-2
High Performance Opal
IP20

Types



Colore



Distribuzione della luce




DiiA® standards
251, 252, 253




direct / indirect
illumination



tunable white
2700 – 6500 K
(optional)



CRI $\geq$ 98
XPECTRUM
(optional)



INO TRIPLE circle suspended



OPAL DALI-2, CRI ≥ 90

SYSTEM	COLOUR TEMP.	COLOUR	LUM. FLUX	ORDER CODE
150.0 W	2700 K	jet black	↓13900 lm	0 3 4 - 3 8 4 5 4 3 8 H
		pure white	↓16500 lm	0 3 4 - 3 8 4 5 4 3 7 H
		special colours	↓15200 lm	0 3 4 - 3 8 4 5 4 3 X H
		white aluminium	↓15200 lm	0 3 4 - 3 8 4 5 4 3 G H
	3000 K	jet black	↓14600 lm	0 3 4 - 3 8 4 5 5 3 8 H
		pure white	↓17300 lm	0 3 4 - 3 8 4 5 5 3 7 H
		special colours	↓16000 lm	0 3 4 - 3 8 4 5 5 3 X H
		white aluminium	↓16000 lm	0 3 4 - 3 8 4 5 5 3 G H
	4000 K	jet black	↓15300 lm	0 3 4 - 3 8 4 5 6 3 8 H
		pure white	↓18100 lm	0 3 4 - 3 8 4 5 6 3 7 H
		special colours	↓16700 lm	0 3 4 - 3 8 4 5 6 3 X H
		white aluminium	↓16700 lm	0 3 4 - 3 8 4 5 6 3 G H

Order options

COLOUR	
pure white	RAL 9010
jet black	RAL 9005
white aluminium	RAL 9006