

## NOBA

suspended


**EN** Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

**IT** Apparecchio a sospensione decorativo in alluminio; superficie cromata lucida, alluminio spazzolato o verniciata a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; lente di vetro piano-convesso di qualità; assenza di ombre multiple; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori

### Quickinfo

2700 K, 3000 K, 4000 K  
CRI ≥ 90  
up to 130 lm/W  
L90 @ 50 000 h  
non DIM, DALI-2

### Types



### Canopy colours



standard


### Luminaire colours



### Light distribution



direct



free positioning by  
cable and hook



high quality  
glass lens

## Order options

## COLOUR TEMPERATURE

2700 K	9
3000 K	0
4000 K	1

## MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

## CABLE COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

## MATERIAL COLOUR


## CANOPY/ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

## BEAM ANGLE


wide flood 67°

## NOBA suspended




## NOBA 40 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	726 lm	0 4 9 - 5 3 1 0 :: 1 ■ ■ W
36 Vf 150 mA	3000 K	755 lm	
	4000 K	790 lm	



## NOBA 50 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	752 lm	0 4 9 - 5 3 1 3 :: 1 ■ ■ W
36 Vf 150 mA	3000 K	782 lm	
	4000 K	819 lm	



## NOBA 60 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	765 lm	0 4 9 - 5 3 1 6 :: 1 ■ ■ W
36 Vf 150 mA	3000 K	796 lm	
	4000 K	833 lm	



## CANOPY CEILING 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
150 mA   non DIM	η 79 %	115-29	0 0 5 - 2 6 0 1 2 1 ■
150 mA   DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 1 2 3 ■



## MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2–25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 0 5 - 3 5 2 1 1 1 ■



## MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9–25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 0 5 - 3 5 1 1 1 1 7



## SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting set trimless

## Mounting accessories



## HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	0 3 0 - 1 0 0 0 1 ■

## Electrical accessories

## POWER SUPPLY 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
150 mA   non DIM	η 80 %	93-36-25	0 0 2 - 9 0 8 1 0
150 mA   DALI-2	η 80 %	112-29-21	0 0 2 - 9 0 8 1 1

\*DALI-2 power supply needed

## DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160 W   48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1–2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200–1050 mA settable const. current		
2 × 42 W   48 V DC   U <sub>OUT</sub> 10–40 V		

**INSET POWER** is the current consumption excluding any ballast

**LUMINOUS FLUX** value calculated for CRI ≥ 90, colour white