

SPADO 150 square

recessed

EN Square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; symmetric radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system

IT Corpo illuminante quadrato in pressofusione di alluminio; con bordo perimetrale; per soffitti di spessore 2-25 mm; verniciatura a polvere; montaggio senza utensili con chiusura a molla a scatto; riflettore in policarbonato, cromo lucido; emissione simmetrica; superficie di emissione arretrata; LED ad efficienza energetica con elevata resa cromatica; converter esterno da inserire nel soffitto, cablaggio passante adatto; alimentatore compatibile con funzionamento a batteria centrale

Quickinfo

3000 K, 4000 K
 CRI \geq 80 / 3 SDCM (initial MacAdam)
 UGR \leq 19
 fino a 118 lm/W
 L80 / 50000 h, L90 / 50000 h
 DALI-2, non DIM
 front IP44, back IP20

Types



Colore



Distribuzione della luce




DiiA® standards
 251, 252, 253



glare control
 (UGR \leq 19)



splash water
 protection
 (IP44)



SPADO 150 square downlight trim



WIDE FLOOD 56°, traffic white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
16.4 W	3000 K	1830 lm	112 lm/W	0 4 9 - 3 1 5 1 5 7 0
	4000 K	1940 lm	118 lm/W	0 4 9 - 3 1 5 1 6 7 0
27.5 W	3000 K	2990 lm	109 lm/W	0 4 9 - 3 1 5 2 5 7 0
	4000 K	3170 lm	115 lm/W	0 4 9 - 3 1 5 2 6 7 0



Mounting accessories (optional)

EXPOSED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
400-260-160	0 4 9 - 3 1 9 2 2 1 0

PRIMED CONCRETE MOUNTING HOUSING

L·W (mm)	ORDER CODE
310-170	0 4 9 - 3 1 9 1 4 1 0

Order options

CONTROL		COLOUR	
non DIM	1	traffic white	RAL 9016
DALI-2	3		