
Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 25
fino a 136 lm/W
L85 / 50000 h
DALI-2, non DIM
Opal
IP50

Types



Colours

Distribuzione della luce

SONO FLEX

recessed

EN Round recessed luminaire in aluminium, consisting of (SONO) light housing and recessed housing; housing with trim suitable for installation in plasterboard ceilings; suitable for ceiling thickness of 10-25 mm; optionally: installation in concrete ceilings with a special installation housing (available as an accessory); surface powder coated; luminaire installs in housing without tools optionally flush or protruding by 25 mm; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

IT Apparecchio da incasso rotondo in alluminio, costituito da corpo illuminante (SONO) e telaio da incasso; telaio da incasso con bordo perimetrale adatto a soffitti di cartongesso; per soffitti di spessore 10-25 mm; in opzione: incasso in calcestruzzo con apposita armatura (disponibile come accessorio); verniciatura a polvere; apparecchio montabile nel telaio senza utensili, a scelta a filo soffitto o sporgente di 25 mm; diffusore satinato in PMMA a illuminazione assolutamente omogenea; stessa luminosità nei modelli di tutte le dimensioni; LED ad efficienza energetica con elevata resa cromatica; apparecchio con 2 ingressi cavi e morsetto per cablaggio passante



DiiA® standards 251, 252, 253




flexible jut out 0 or 25 mm




dust & insect protection (IP 50)



tunable white 2700 – 6500 K (optional)



365 150




SONO FLEX 350 TRIM


CRI ≥ 80 | 220-240 V | DALI 1 ADDR. | IP50 | X-PERT

OPAL pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	1940 lm	122 lm/W	063-323857O
	4000 K	2050 lm	129 lm/W	063-323867O



465 150




SONO FLEX 450 TRIM

CRI ≥ 80 | 220-240 V | DALI 1 ADDR. | IP50 | X-PERT

OPAL pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	2840 lm	122 lm/W	063-324857O
	4000 K	3010 lm	130 lm/W	063-324867O



615 150



SONO FLEX 600 TRIM

CRI ≥ 80 | 220-240 V | DALI 1 ADDR. | IP50 | X-PERT


OPAL pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
42.0 W	3000 K	5410 lm	129 lm/W	063-325857O
	4000 K	5730 lm	136 lm/W	063-325867O

Order options

CONTROL		COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		

Mounting accessories



CONCRETE INSTALLATION HOUSING

TYPE	Ø·H (mm)	ORDER CODE
for SONO FLEX 350	364·107	0 6 3 - 2 2 3 8 1 0 0
for SONO FLEX 450	464·107	0 6 3 - 2 2 4 8 1 0 0
for SONO FLEX 600	614·107	0 6 3 - 2 2 5 8 1 0 0

Mounting tools accessories

DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0

Volksschule Erlaaer

Austria

Architetto
ARGE Architekten
Kronaus – Mitterer/
Vasko & Partner

Fotografo
Romana Fürnkranz
Architekturfotografie
Wien



Prodotti utilizzati



SONO FLEX
recessed

No liability is assumed for
typographical or printing errors.
© XAL GmbH · Auer-Welsbach-
Gasse 36 · 8055 Graz · Austria ·
www.xal.com





LKH Graz Stroke Unit

Austria

Architetto
DI Michael Pansinger,
KAGes

Lighting Design
XAL

Fotografo
Kurt Kuball



Prodotti utilizzati



SONO FLEX recessed



RECOVER

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



