








Quickinfo

2700 K, 3000 K, 3500 K
CRI ≥ 90 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
fino a 110 lm/W
L85 / 50000 h, L90 / 100000 h
DALI-2, non DIM
IP20

Types



Colours



Distribuzione della luce



BO semi-recessed / surface

EN Cylindrical spotlight made of aluminium; surface powder coated; either with surface mounted housing or as ceiling recessed variant; spotlight head 350° rotatable and 90° tiltable; with optional high-quality lens system with precise radiation characteristic; or high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; good glare reduction due to recessed light point plane; optical attachments as accessories; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering

IT Faretto cilindrico in alluminio; verniciatura a polvere; a scelta con armatura a plafone o da incasso; testata girevole 350° e orient. 90°; a scelta con ottica lenticolare di precisione; oppure riflettore d'alta qualità con ottica sfaccettata in alluminio applicato a vapore; curva fotometrica precisa con diversi angoli di emissione; ottima schermatura con superficie di emissione arretrata; unità ottiche come accessori; con tecnologia COB (Chip on Board) o LED high power per la massima efficienza; assenza di ombre multiple; LED ad efficienza energetica con elevata resa cromatica



glare control via honeycomb louver




350° rotatable, 90° tiltable



CRI ≥ 95 2 SDCM (optional)





BO 32 semi-recessed

90° 350° | CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT

SPOT 18°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W,	2700 K	788 lm	91 lm/W	049-612041 S
36 Vf,	3000 K	817 lm	94 lm/W	049-612051 S
250 mA	3500 K	835 lm	96 lm/W	049-612071 S


MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W,	2700 K	821 lm	94 lm/W	049-612041 M
36 Vf,	3000 K	852 lm	98 lm/W	049-612051 M
250 mA	3500 K	870 lm	100 lm/W	049-612071 M

FLOOD 34°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W,	2700 K	783 lm	90 lm/W	049-612041 F
36 Vf,	3000 K	813 lm	93 lm/W	049-612051 F
250 mA	3500 K	830 lm	96 lm/W	049-612071 F





BO 45 semi-recessed

90° 350° | CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT

SUPER SPOT 8°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.9 W,	2700 K	406 lm	59 lm/W	049-613041 V
11 Vf,	3000 K	432 lm	63 lm/W	049-613051 V
600 mA	3500 K	432 lm	63 lm/W	049-613071 V

SPOT 12°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.7 W,	2700 K	1140 lm	89 lm/W	049-613041 S
37 Vf,	3000 K	1180 lm	93 lm/W	049-613051 S
350 mA	3500 K	1200 lm	95 lm/W	049-613071 S

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W,	2700 K	1350 lm	101 lm/W	049-613041 M
36 Vf,	3000 K	1410 lm	105 lm/W	049-613051 M
400 mA	3500 K	1440 lm	107 lm/W	049-613071 M

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8
special colours	X


FLOOD 36°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W,	2700 K	1390 lm	103 lm/W	0 4 9 - 6 1 3 0 4 1 ◪ F
36 Vf,	3000 K	1440 lm	107 lm/W	0 4 9 - 6 1 3 0 5 1 ◪ F
400 mA	3500 K	1470 lm	110 lm/W	0 4 9 - 6 1 3 0 7 1 ◪ F



BO 55 semi-recessed





SPOT 17°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.9 W,	2700 K	1980 lm	95 lm/W	0 4 9 - 6 1 4 0 4 1 ◪ S
36 Vf,	3000 K	2060 lm	99 lm/W	0 4 9 - 6 1 4 0 5 1 ◪ S
600 mA	3500 K	2110 lm	101 lm/W	0 4 9 - 6 1 4 0 7 1 ◪ S

MEDIUM 31°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.9 W,	2700 K	2000 lm	96 lm/W	0 4 9 - 6 1 4 0 4 1 ◪ M
36 Vf,	3000 K	2080 lm	100 lm/W	0 4 9 - 6 1 4 0 5 1 ◪ M
600 mA	3500 K	2130 lm	102 lm/W	0 4 9 - 6 1 4 0 7 1 ◪ M


FLOOD 37°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.9 W,	2700 K	2010 lm	97 lm/W	0 4 9 - 6 1 4 0 4 1 ◪ F
36 Vf,	3000 K	2090 lm	100 lm/W	0 4 9 - 6 1 4 0 5 1 ◪ F
600 mA	3500 K	2140 lm	103 lm/W	0 4 9 - 6 1 4 0 7 1 ◪ F



BO 32 surface





SPOT 18°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W,	2700 K	788 lm	91 lm/W	0 4 9 - 6 2 2 0 4 1 ◪ S
36 Vf,	3000 K	817 lm	94 lm/W	0 4 9 - 6 2 2 0 5 1 ◪ S
250 mA	3500 K	835 lm	96 lm/W	0 4 9 - 6 2 2 0 7 1 ◪ S

revision opening for power supply required

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W,	2700 K	821 lm	94 lm/W	0 4 9 - 6 2 2 0 4 1 ◪ M
36 Vf,	3000 K	852 lm	98 lm/W	0 4 9 - 6 2 2 0 5 1 ◪ M
250 mA	3500 K	870 lm	100 lm/W	0 4 9 - 6 2 2 0 7 1 ◪ M

revision opening for power supply required

Order options

COLOUR	◪
traffic white RAL 9016	7
jet black RAL 9005	8
special colours	X

FLOOD 34°, CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W,	2700 K	783 lm	90 lm/W	0 4 9 - 6 2 2 0 4 1 ◪ F
36 Vf,	3000 K	813 lm	93 lm/W	0 4 9 - 6 2 2 0 5 1 ◪ F
250 mA	3500 K	830 lm	96 lm/W	0 4 9 - 6 2 2 0 7 1 ◪ F

revision opening for power supply required



BO 45 surface





SUPER SPOT 8°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.9 W,	2700 K	406 lm	59 lm/W	0 4 9 - 6 2 3 0 4 1 ◪ V
11 Vf,	3000 K	432 lm	63 lm/W	0 4 9 - 6 2 3 0 5 1 ◪ V
600 mA	3500 K	432 lm	63 lm/W	0 4 9 - 6 2 3 0 7 1 ◪ V

revision opening for power supply required

SPOT 12°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.7 W,	2700 K	1140 lm	89 lm/W	0 4 9 - 6 2 3 0 4 1 ◪ S
37 Vf,	3000 K	1180 lm	93 lm/W	0 4 9 - 6 2 3 0 5 1 ◪ S
350 mA	3500 K	1200 lm	95 lm/W	0 4 9 - 6 2 3 0 7 1 ◪ S

revision opening for power supply required

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W,	2700 K	1350 lm	101 lm/W	0 4 9 - 6 2 3 0 4 1 ◪ M
36 Vf,	3000 K	1410 lm	105 lm/W	0 4 9 - 6 2 3 0 5 1 ◪ M
400 mA	3500 K	1440 lm	107 lm/W	0 4 9 - 6 2 3 0 7 1 ◪ M

revision opening for power supply required

FLOOD 36°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W,	2700 K	1390 lm	103 lm/W	0 4 9 - 6 2 3 0 4 1 ◪ F
36 Vf,	3000 K	1440 lm	107 lm/W	0 4 9 - 6 2 3 0 5 1 ◪ F
400 mA	3500 K	1470 lm	110 lm/W	0 4 9 - 6 2 3 0 7 1 ◪ F

revision opening for power supply required

Order options

COLOUR	◪
traffic white RAL 9016	7
jet black RAL 9005	8
special colours	X



BO 55 surface





SPOT 17°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.9 W,	2700 K	1980 lm	95 lm/W	049-624041 S
36 Vf,	3000 K	2060 lm	99 lm/W	049-624051 S
600 mA	3500 K	2110 lm	101 lm/W	049-624071 S

revision opening for power supply required

MEDIUM 31°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.9 W,	2700 K	2000 lm	96 lm/W	049-624041 M
36 Vf,	3000 K	2080 lm	100 lm/W	049-624051 M
600 mA	3500 K	2130 lm	102 lm/W	049-624071 M

revision opening for power supply required

FLOOD 37°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.9 W,	2700 K	2010 lm	97 lm/W	049-624041 F
36 Vf,	3000 K	2090 lm	100 lm/W	049-624051 F
600 mA	3500 K	2140 lm	103 lm/W	049-624071 F

revision opening for power supply required


Electrical accessories (required)

POWER SUPPLY 198-264 V AC

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
350 mA | 15 W | DALI-2 | PC2	η 87 %	166·29·21	002-907220
350 mA | 22 W | non DIM | PC2	η 89 %	180·30·21	002-907222
400 mA | 22 W | non DIM | PC2	η 89 %	180·30·21	002-907224
600 mA | 30 W | non DIM | PC1	η 89 %	180·30·21	002-907226
400 mA | 15 W | DALI-2 | PC2	η 87 %	166·29·21	002-907228
600 mA | 40 W | DALI-2 | PC2	η 89 %	197·29·21	002-907229
250 mA | 10 W | non DIM | PC2	η 80 %	65·39·20	002-907422
250 mA | 10 W | DALI-2 | PC2	η 82 %	166·29·21	002-907423

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10–40 V SELV

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8
special colours	X

Optical accessories (optional)



HONEYCOMB LOUVER for BO 32 | JUST 32 | MOVE IN 32 | TARO 32 | TILA 32

COLOUR	Ø·H (mm)	ORDER CODE
jet black	30·3	007 - 1965168



HONEYCOMB LOUVER for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

COLOUR	Ø·H (mm)	ORDER CODE
jet black	42·3	007 - 1965188



HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø·H (mm)	ORDER CODE
jet black	50·3	007 - 1965598



OVAL LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007 - 1965860



OVAL LENS for BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007 - 1965880

OVAL LENS for BO 55 | JUST 55

Ø·H (mm)	ORDER CODE
50·3	007 - 1965890



SOFT LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007 - 1965960



SOFT LENS for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007 - 1965980

SOFT LENS for BO 55 | JUST 55

Ø·H (mm)	ORDER CODE
50·3	007 - 1965990



WALLWASHER LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007 - 1965760



WALLWASHER LENS for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007 - 1965780

WALLWASHER LENS for BO 55 | JUST 55

Ø·H (mm)	ORDER CODE
50·3	007 - 1965790

Equinix, Amsterdam

Paesi Bassi

Architetto
KABAZ Architects,
Hilversum NL

Fotografo
Kabaz



Prodotti utilizzati



BO semi-recessed / surface



MINO 60 ceiling / suspended system

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









Wohnhaus Pferdeblick, Austria

Austria

Architetto
Baukooperative GmbH

Lighting Design
Baukooperative GmbH

Fotografo
Schreyer David



Prodotti utilizzati



BO semi-recessed / surface



MOVE IT 25 surface / suspended system



JUST 45 MOVE IT 25 / 25 S / 45

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com






SBC





