



Quickinfo

4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 19
fino a ↓ 19.900 lm / ↑ 10.300 lm
fino a 119 lm/W
L90 / 50000 h
Cover: Microprismatic
DALI-2
IP20

Types



Colours

Distribuzione della luce

TASK circle

suspended

EN Ring-shaped suspended luminaire, consisting of single elements in quarter circle or rectangular shape; Luminaire housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, toolless height adjustment; convenient quick mounting system without tools; incl. feeder cable; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; optional acoustic elements available


IT Corpo illuminante a sospensione di forma circolare, composto da singoli elementi in un quarto di cerchio o in una forma rettangolare; Corpo illuminante in alluminio con bordi arrotondati; forma ultrapiatta (solo 15 mm); verniciatura a polvere; cavo regolabile in altezza senza attrezzi; pratico sistema di montaggio rapido senza utensili; incl. cavo di alimentazione; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; in opzione elementi acustici disponibile




DiiA® standards 251, 252, 253




clicksystem



DIN EN 12464-1
UGR ≤ 19



CRI ≥ 98
XPECTRUM
(optional)





TASK circle suspended

CRI ≥ 90 | UGR ≤ 19 | 220-240 V | 4 ADDR. | X-PERT | X-PERT

DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
169.0 W	4000 K	↧13200/↥6870 lm	119 lm/W	0 5 9 - 5 2 8 1 1 3 ◪ K






TASK long circle suspended


CRI ≥ 90 | UGR ≤ 19 | 220-240 V | 6 ADDR. | X-PERT | X-PERT

DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
253.0 W	4000 K	↧19900/↥10300 lm	119 lm/W	0 5 9 - 5 2 8 2 1 3 ◪ K



Planning Information





TASK long circle
252 W, 4000 K, direct / indirect power

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 | 0.5 | 0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE ------

Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H

UGR transversal	≤ 19
UGR axial	≤ 19

Order options


COLOUR ◪	
pure white RAL 9010	7
jet black RAL 9005	8

Compound Semiconductor Applications Catapult, South Wales


Regno Unito

Architetto
Monteith Scott

Fotografo
Richard Kiely



Prodotti utilizzati



TASK circle suspended



MINO 100 ceiling / suspended system

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

https://xal.com/it/esperienza-luce/progetti/pr/compound-semiconductor-applications-catapult-south-wales-282799



