



## TUBO 60

suspended


<sup>EN</sup> Supporting profile in extruded aluminium; end cap in aluminium; surface powder coated; suspended luminaire with cable suspension; height adjustment without tools; incl. feeder cable; light control via high quality lens system for maximum, homogeneous illumination; optionally cylindr. HPO (High Performance Opal) cover or clear, cylindrical cover with linear prismatic optic; energy-efficient LEDs with very good colour rendering

<sup>IT</sup> Binario portante in profilo di alluminio estruso; testata di chiusura in alluminio; verniciatura a polvere; apparecchio con sospensione a fune; regolazione altezza senza utensili; incl. cavo di alimentazione; controllo della luce con ottica lenticolare di alta qualità per un'illum. omogenea; a scelta, cover cilindrica HPO (High Performance Opal) o cover trasparente e cilindrica, con ottica prismatico lineare; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM  
 (initial MacAdam)  
 fino a 3,280 lm/m  
 fino a 142 lm/W  
 L90 / 50000 h  
 DALI-2  
 Clear Cover, High Performance  
 Opal  
 IP20

### Types



### Colore




### Distribuzione della luce




driver  
integrated



system solution



uniform  
illumination




### TUBO 60 opal suspended



#### OPAL DALI-2

| SYSTEM | LENGTH  | COLOUR TEMP. | CRI ≥ | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|---------|--------------|-------|-----------|----------|---|
| 13.9 W | 625 mm  | 3000 K       | 80    | 1700 lm   | 122 lm/W | 0 5 8 - 3 2 1 2 5 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 1480 lm   | 106 lm/W | 0 5 8 - 3 2 1 2 0 3 <input checked="" type="checkbox"/> O |
|        |         | 4000 K       | 80    | 1810 lm   | 130 lm/W | 0 5 8 - 3 2 1 2 6 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 1480 lm   | 106 lm/W | 0 5 8 - 3 2 1 2 1 3 <input checked="" type="checkbox"/> O |
| 27.9 W | 1210 mm | 3000 K       | 80    | 3400 lm   | 122 lm/W | 0 5 8 - 3 2 1 4 5 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 2960 lm   | 106 lm/W | 0 5 8 - 3 2 1 4 0 3 <input checked="" type="checkbox"/> O |
|        |         | 4000 K       | 80    | 3620 lm   | 130 lm/W | 0 5 8 - 3 2 1 4 6 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 2960 lm   | 106 lm/W | 0 5 8 - 3 2 1 4 1 3 <input checked="" type="checkbox"/> O |
| 34.0 W | 1500 mm | 3000 K       | 80    | 4220 lm   | 124 lm/W | 0 5 8 - 3 2 1 5 5 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 3670 lm   | 108 lm/W | 0 5 8 - 3 2 1 5 0 3 <input checked="" type="checkbox"/> O |
|        |         | 4000 K       | 80    | 4490 lm   | 132 lm/W | 0 5 8 - 3 2 1 5 6 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 3670 lm   | 108 lm/W | 0 5 8 - 3 2 1 5 1 3 <input checked="" type="checkbox"/> O |
| 54.0 W | 2375 mm | 3000 K       | 80    | 6740 lm   | 125 lm/W | 0 5 8 - 3 2 1 8 5 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 5870 lm   | 109 lm/W | 0 5 8 - 3 2 1 8 0 3 <input checked="" type="checkbox"/> O |
|        |         | 4000 K       | 80    | 7170 lm   | 133 lm/W | 0 5 8 - 3 2 1 8 6 3 <input checked="" type="checkbox"/> O |
|        |         |              | 90    | 5870 lm   | 109 lm/W | 0 5 8 - 3 2 1 8 1 3 <input checked="" type="checkbox"/> O |




### TUBO 60 ribbed suspended



#### CLEAR COVER WITH LINEAR PRISMATIC OPTIC DALI-2

| SYSTEM | LENGTH  | COLOUR TEMP. | CRI ≥ | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|---------|--------------|-------|-----------|----------|---|
| 13.9 W | 625 mm  | 3000 K       | 80    | 1820 lm   | 131 lm/W | 0 5 8 - 5 2 1 2 5 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 1580 lm   | 114 lm/W | 0 5 8 - 5 2 1 2 0 3 <input checked="" type="checkbox"/> C |
|        |         | 4000 K       | 80    | 1940 lm   | 140 lm/W | 0 5 8 - 5 2 1 2 6 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 1580 lm   | 114 lm/W | 0 5 8 - 5 2 1 2 1 3 <input checked="" type="checkbox"/> C |
| 27.9 W | 1210 mm | 3000 K       | 80    | 3640 lm   | 130 lm/W | 0 5 8 - 5 2 1 4 5 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 3170 lm   | 114 lm/W | 0 5 8 - 5 2 1 4 0 3 <input checked="" type="checkbox"/> C |
|        |         | 4000 K       | 80    | 3870 lm   | 139 lm/W | 0 5 8 - 5 2 1 4 6 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 3170 lm   | 114 lm/W | 0 5 8 - 5 2 1 4 1 3 <input checked="" type="checkbox"/> C |
| 34.0 W | 1500 mm | 3000 K       | 80    | 4510 lm   | 133 lm/W | 0 5 8 - 5 2 1 5 5 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 3930 lm   | 116 lm/W | 0 5 8 - 5 2 1 5 0 3 <input checked="" type="checkbox"/> C |
|        |         | 4000 K       | 80    | 4800 lm   | 141 lm/W | 0 5 8 - 5 2 1 5 6 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 3930 lm   | 116 lm/W | 0 5 8 - 5 2 1 5 1 3 <input checked="" type="checkbox"/> C |
| 54.0 W | 2375 mm | 3000 K       | 80    | 7210 lm   | 134 lm/W | 0 5 8 - 5 2 1 8 5 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 6280 lm   | 116 lm/W | 0 5 8 - 5 2 1 8 0 3 <input checked="" type="checkbox"/> C |
|        |         | 4000 K       | 80    | 7680 lm   | 142 lm/W | 0 5 8 - 5 2 1 8 6 3 <input checked="" type="checkbox"/> C |
|        |         |              | 90    | 6280 lm   | 116 lm/W | 0 5 8 - 5 2 1 8 1 3 <input checked="" type="checkbox"/> C |



#### Order options

| COLOUR              |                                       |
|---------------------|---------------------------------------|
| pure white RAL 9010 | 7 <input checked="" type="checkbox"/> |
| jet black RAL 9005  | 8 <input checked="" type="checkbox"/> |

# Office, Amsterdam


Paesi Bassi

**Architetto**  
MVSA Architects

**Fotografo**  
Kris Dekeijser



## Prodotti utilizzati



## TUBO 60 suspended

