



SONIC

free standing


^{EN} Free standing luminaire with conical luminaire head in die-cast aluminium; surface powder coated; round aluminium downpipe arranged centralised or decentralised; round pedestal with recess for table base; direct / indirect light distribution; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; incl. connection cable (3m) with safety plug; Acoustic elements made of high quality, self-supporting, at least 50% recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties available

^{IT} Piantana con testata conica in alluminio pressofuso; verniciatura a polvere; stelo rotondo in alluminio a scelta con disposizione centrale o laterale; piedistallo rotondo con apertura per piede tavolo; emissione diretta/indiretta; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; opzionale: componente di luce indiretta con piastre proprie inclinate per un'emissione asimmetrica; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; incl. cavo di collegamento (3 m) con spina Schuko; Elementi acustici in feltro prodotto con PET riciclato per almeno il 50%, alta qualità e autoportante (alte prestazioni acustiche grazie al materiale doppiato) o come paralume acusticamente efficace (ampia scelta di colori) con proprietà fonoassorbenti disponibili

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM (initial MacAdam)
 UGR ≤ 16, UGR ≤ 19
 fino a ↓ 5,290 lm / ↑ 10,300 lm
 fino a 159 lm/W
 L90 / 50000 h
 DIM touch sul palo, interruttore non dimmerabile, sensore ESSENTIAL autonomo
 Microprismatic
 IP20

Types




Colore



Distribuzione della luce



DiiA® standards
 251, 252, 253



microprismatic
 UGR ≤ 19



sensor version
 available



direct / indirect
 illumination




SONIC free standing centric pole



DIRECT / INDIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
66.0 W	3000 K	↓5000/↑4940 lm	151 lm/W	0 5 9 - 7 9 2 1 5 <input checked="" type="checkbox"/> P
	4000 K	↓5290/↑5230 lm	159 lm/W	0 5 9 - 7 9 2 1 6 <input checked="" type="checkbox"/> P



DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
104.0 W	3000 K	↓4260/↑9620 lm	133 lm/W	0 5 9 - 7 9 4 1 5 <input checked="" type="checkbox"/> P
	4000 K	↓4510/↑10300 lm	142 lm/W	0 5 9 - 7 9 4 1 6 <input checked="" type="checkbox"/> P




SONIC free standing excentric pole



DIRECT / INDIRECT CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
66.0 W	3000 K	↓5000/↑4940 lm	151 lm/W	0 5 9 - 7 9 2 2 5 <input checked="" type="checkbox"/> P
	4000 K	↓5290/↑5230 lm	159 lm/W	0 5 9 - 7 9 2 2 6 <input checked="" type="checkbox"/> P



DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
104.0 W	3000 K	↓4260/↑9620 lm	133 lm/W	0 5 9 - 7 9 4 2 5 <input checked="" type="checkbox"/> P
	4000 K	↓4510/↑10300 lm	142 lm/W	0 5 9 - 7 9 4 2 6 <input checked="" type="checkbox"/> P

Planning Information



SONIC excentric pole free standing
69W, 4000K, direct/indirect

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6



GLARE EVALUATION


Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Order options

CONTROL		COLOUR	
non DIM switch	1	special colours	X
touch DIM on pole	5	black grey RAL 7021	6
stand alone ESSENTIAL sensor	7	pure white RAL 9010	7

Acoustic accessories (optional)

ABSORBER RING 1050



COLOUR	Ø-H (mm)	ORDER CODE
anthracite	1050-50	0 5 9 - 7 7 1 1 2 1 B
marble grey	1050-50	0 5 9 - 7 7 1 1 2 1 D
black	1050-50	0 5 9 - 7 7 1 1 2 1 L
limestone	1050-50	0 5 9 - 7 7 1 1 2 1 S
white	1050-50	0 5 9 - 7 7 1 1 2 1 W
felt grey	1050-50	0 5 9 - 7 7 1 1 2 1 G

only in combination with SONIC suspended or SONIC free standing

ABSORBER RING 1280



COLOUR	Ø-H (mm)	ORDER CODE
anthracite	1280-50	0 5 9 - 7 7 1 1 1 1 B
marble grey	1280-50	0 5 9 - 7 7 1 1 1 1 D
black	1280-50	0 5 9 - 7 7 1 1 1 1 L
limestone	1280-50	0 5 9 - 7 7 1 1 1 1 S
white	1280-50	0 5 9 - 7 7 1 1 1 1 W
felt grey	1280-50	0 5 9 - 7 7 1 1 1 1 G

only in combination with SONIC suspended or SONIC free standing

SOUNDCAP



COLOUR	Ø-H (mm)	ORDER CODE
marble grey	527-300	0 5 9 - 7 7 3 1 1 1 D
felt grey	527-300	0 5 9 - 7 7 3 1 1 1 G
black	527-300	0 5 9 - 7 7 3 1 1 1 L
white	527-300	0 5 9 - 7 7 3 1 1 1 W
acoustic special colours	527-300	0 5 9 - 7 7 3 1 1 1 X

only in combination with SONIC suspended or SONIC free standing; bracket colour white; other bracket colours on request

Order options

CONTROL		COLOUR	
non DIM switch	1	special colours	X
touch DIM on pole	5	black grey RAL 7021	6
stand alone ESSENTIAL sensor	7	pure white RAL 9010	7

Borealis AG, Vienna

Austria

Architetto

burghardt zt gesmbh

Fotografo

Kurt Kuball



Prodotti utilizzati



SONIC free standing



