



TASK

free standing


^{EN} Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

^{IT} Piantana di alluminio con testata rettangolare e bordi arrotondati; forma ultrapiatta (solo 15 mm); stelo rettangolare; piedistallo con apertura per piede tavolo; verniciatura a polvere; distribuzione della luce diretta/indiretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente direzionata in basso e su tramite incisione laser; opzionale: componente di luce indiretta con piastre proprie per un flusso luminoso potenziato; opzionale: componente di luce indiretta con piastre proprie inclinate per un'emissione asimmetrica; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; interruttore integrato nello stelo; incl. cavo di collegamento (3 m) con spina Schuko

Quickinfo

3000 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAdam)
 UGR \leq 10, UGR \leq 13, UGR \leq 19
 fino a ↓ 4,370 lm / ↑ 9,320 lm
 fino a 136 lm/W
 L90 / 50000 h
 DIM touch sul palo, Loxone Air /
 DIM touch sul palo, Loxone Air /
 ESSENTIAL sensor, sensore
 ESSENTIAL autonomo
 Microprismatic
 IP20

Types



Colore



Distribuzione della luce




suitable for
double
workstation




SENSE sensor
on request



lighting control
by touch DIM on
pole



tunable white
2700 – 6500 K



CRI \geq 98
XPECTRUM
(optional)




TASK free standing u-shape



MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|----------------|----------|---|
| 67.0 W | 3000 K | ↓4100/↑3350 lm | 111 lm/W | 0 5 9 - 2 9 4 3 0 <input checked="" type="checkbox"/> Z |
| | 4000 K | ↓4370/↑3560 lm | 118 lm/W | 0 5 9 - 2 9 4 3 1 <input checked="" type="checkbox"/> Z |



MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|----------------|----------|---|
| 76.0 W | 3000 K | ↓2400/↑7330 lm | 128 lm/W | 0 5 9 - 2 9 4 2 0 <input checked="" type="checkbox"/> Z |
| | 4000 K | ↓2550/↑7800 lm | 136 lm/W | 0 5 9 - 2 9 4 2 1 <input checked="" type="checkbox"/> Z |

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|----------------|----------|---|
| 94.0 W | 3000 K | ↓1900/↑8630 lm | 112 lm/W | 0 5 9 - 2 9 4 1 0 <input checked="" type="checkbox"/> Z |
| | 4000 K | ↓2030/↑9320 lm | 121 lm/W | 0 5 9 - 2 9 4 1 1 <input checked="" type="checkbox"/> Z |




TASK free standing t-shape



MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|----------------|----------|---|
| 67.0 W | 3000 K | ↓4100/↑3350 lm | 111 lm/W | 0 5 9 - 2 9 5 3 0 <input checked="" type="checkbox"/> Z |
| | 4000 K | ↓4370/↑3560 lm | 118 lm/W | 0 5 9 - 2 9 5 3 1 <input checked="" type="checkbox"/> Z |



MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|----------------|----------|---|
| 76.0 W | 3000 K | ↓2400/↑7330 lm | 128 lm/W | 0 5 9 - 2 9 5 2 0 <input checked="" type="checkbox"/> Z |
| | 4000 K | ↓2550/↑7800 lm | 136 lm/W | 0 5 9 - 2 9 5 2 1 <input checked="" type="checkbox"/> Z |

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|----------------|----------|---|
| 94.0 W | 3000 K | ↓1900/↑8630 lm | 112 lm/W | 0 5 9 - 2 9 5 1 0 <input checked="" type="checkbox"/> Z |
| | 4000 K | ↓2030/↑9320 lm | 121 lm/W | 0 5 9 - 2 9 5 1 1 <input checked="" type="checkbox"/> Z |

Order options

| CONTROL | | COLOUR | |
|--------------------------------|---|--------------------------|---|
| Loxone Air / ESSENTIAL sensor | S | white aluminium RAL 9006 | 6 |
| Loxone Air / touch DIM on pole | T | pure white RAL 9010 | 7 |
| touch DIM on pole | 5 | jet black RAL 9005 | 8 |
| stand alone ESSENTIAL sensor | 7 | special colours | X |

OFFICE OMV

Austria

Fotografo
Kurt Kuball



Prodotti utilizzati



TASK free standing

