


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 19
fino a ↓ 4.370 lm / ↑ 9.320 lm
fino a 136 lm/W
L90 / 50000 h
DIM touch sul palo, Loxone Air / DIM touch sul palo, Loxone Air / ESSENTIAL sensor, sensore ESSENTIAL autonomo
Microprismatic
IP20

Types




Colours



Distribuzione della luce






suitable for double workstation




SENSE sensor on request



lighting control by touch DIM on pole



tunable white 2700 – 6500 K



CRI ≥ 98 XPECTRUM (optional)


TASK

free standing

EN Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

IT Piantana di alluminio con testata rettangolare e bordi arrotondati; forma ultrapiatta (solo 15 mm); stelo rettangolare; piedistallo con apertura per piede tavolo; verniciatura a polvere; distribuzione della luce diretta/indiretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente direzionata in basso e e su tramite incisione laser; opzionale: componente di luce indiretta con piastre proprie per un flusso luminoso potenziato; opzionale: componente di luce indiretta con piastre proprie inclinate per un'emissione asimmetrica; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; interruttore integrato nello stelo; incl. cavo di collegamento (3 m) con spina Schuko





TASK free standing u-shape

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 3000 | 220-240 V | X-PERT | X-PERT | presence | brightness

MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↧4100/↥3350 lm	111 lm/W	059-29430 ◆ ◪ Z
	4000 K	↧4370/↥3560 lm	118 lm/W	059-29431 ◆ ◪ Z


MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↧2400/↥7330 lm	128 lm/W	059-29420 ◆ ◪ Z
	4000 K	↧2550/↥7800 lm	136 lm/W	059-29421 ◆ ◪ Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↧1900/↥8630 lm	112 lm/W	059-29410 ◆ ◪ Z
	4000 K	↧2030/↥9320 lm	121 lm/W	059-29411 ◆ ◪ Z





TASK free standing t-shape

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 3000 | 220-240 V | X-PERT | X-PERT | presence | brightness

MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↧4100/↥3350 lm	111 lm/W	059-29530 ◆ ◪ Z
	4000 K	↧4370/↥3560 lm	118 lm/W	059-29531 ◆ ◪ Z

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↧2400/↥7330 lm	128 lm/W	059-29520 ◆ ◪ Z
	4000 K	↧2550/↥7800 lm	136 lm/W	059-29521 ◆ ◪ Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↧1900/↥8630 lm	112 lm/W	059-29510 ◆ ◪ Z
	4000 K	↧2030/↥9320 lm	121 lm/W	059-29511 ◆ ◪ Z

Order options

CONTROL ◆		COLOUR ◪	
touch DIM on pole	5	white aluminium RAL 9006	6
stand alone ESSENTIAL sensor	7	pure white RAL 9010	7
Loxone Air / ESSENTIAL sensor	S	jet black RAL 9005	8
Loxone Air / touch DIM on pole	T	special colours	X

OFFICE OMV

Austria

Fotografo
Kurt Kuball



Prodotti utilizzati



TASK free standing

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









