



TASK square

free standing


^{EN} Free standing luminaire with square luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); steel round downpipe; pedestal with recess for table base; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

^{IT} Piantana di alluminio con testata quadrata e bordi arrotondati; forma ultrapiatta (solo 15 mm); stelo di acciaio rotondo; piedistallo con apertura per piede tavolo; verniciatura a polvere; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; interruttore integrato nello stelo; incl. cavo di collegamento (3 m) con spina Schuko

Quickinfo

3000 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAdam)
 UGR \leq 10
 fino a ↓ 2,420 lm / ↑ 10,700 lm
 fino a 143 lm/W
 L90 / 50000 h
 DIM touch sul palo, sensore ESSENTIAL autonomo
 Microprismatic
 IP20

Types



Colore




Distribuzione della luce



suitable for
fourfold
workstation



lighting control
by touch DIM on
pole



CRI \geq 98
XPECTRUM
(optional)




TASK square free standing




DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
92.0 W	3000 K	↓2280/↑10000 lm	133 lm/W	0 5 9 - 2 9 3 2 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2420/↑10700 lm	143 lm/W	0 5 9 - 2 9 3 2 1 <input checked="" type="checkbox"/> Z



Planning Information



TASK square free standing

92W, 4000K, direct/indirect power

ROOM VALUES

Room dimensions	7.2 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	4.8 × 0.6 m
Surface height	0.75 m
Average illuminance (E _m)	> 500 lx

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
65° ≤ 3000 cd/m²	



Order options

CONTROL		COLOUR	
touch DIM on pole	5	special colours	X
stand alone ESSENTIAL sensor	7	white aluminium RAL 9006	6
		pure white RAL 9010	7
		jet black RAL 9005	8

Office MyHammer

Germania

Architetto

designfunktion
Gesellschaft für
moderne Einrichtung
Berlin mbH

Fotografo

Werner Huthmacher



Prodotti utilizzati



**TASK square free
standing**

