

Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 10
fino a ↓ 2.420 lm / ↑ 10.700 lm
fino a 143 lm/W
L90 / 50000 h
DIM touch sul palo, sensore
ESSENTIAL autonomo
Microprismatic
IP20

Types



Colours

Distribuzione della luce

TASK square

free standing

EN Free standing luminaire with square luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); steel round downpipe; pedestal with recess for table base; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

IT Piantana di alluminio con testata quadrata e bordi arrotondati; forma ultrapiatta (solo 15 mm); stelo di acciaio rotondo; piedistallo con apertura per piede tavolo; verniciatura a polvere; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; percentuale indiretta con piastre a flusso luminoso potenziato e massima illuminazione del soffitto; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; interruttore integrato nello stelo; incl. cavo di collegamento (3 m) con spina Schuko



suitable for fourfold workstation



lighting control by touch DIM on pole



CRI ≥ 98 XPECTRUM (optional)



TASK square free standing

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 1500 | 220-240 V | X-PERT | X-PERT | presence | brightness

DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
92.0 W	3000 K	↧2280/↥10000 lm	133 lm/W	059-29320 ◆ ◪ Z
	4000 K	↧2420/↥10700 lm	143 lm/W	059-29321 ◆ ◪ Z



Planning Information





TASK square free standing
92 W, 4000 K, direct / indirect power

ROOM VALUES

Room dimensions	7.2 × 4 × 2.8 m
Reflection factor	0.7 | 0.5 | 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	4.8 × 0.6 m
Surface height	0.75 m
Average illuminance (E_m)	> 500 lx

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H

UGR transversal	≤ 19
UGR axial	≤ 19

65° ≤ 3000 cd/m²

Order options

CONTROL ◆	
touch DIM on pole	5
stand alone ESSENTIAL sensor	7

COLOUR ◪	
white aluminium RAL 9006	6
pure white RAL 9010	7
jet black RAL 9005	8
special colours	X

Office MyHammer

Germania

Architetto
designfunktion
Gesellschaft für
moderne Einrichtung
Berlin mbH

Fotografo
Werner Huthmacher



Prodotti utilizzati



TASK square free standing

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



