


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
fino a 100 lm/W
L95 / 50000 h
touch DIM / sensore stand alone
Opal
IP20

Types



Colours

Montaggio

Distribuzione della luce

TASK

table

EN Desk lamp in puristic design with high functionality; lamp head 360° rotatable and +/- 15° tiltable; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; continuously adjustable dimming via optical sensor (10-100 % analog); integrated USB charging socket for charging of a smart device; version with presence detector

IT Apparecchio da scrivania di design sobrio ed elevata funzionalità; testata girevole di 360° e orientabile di +/- 15°; verniciatura a polvere; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; dimming continuo con sensore ottico (10-100 % analogico); con porta USB per caricare smart devices; modello con segnalatore di presenza



360° rotatable,
± 15° tiltable



presence sensor



USB charging socket




TASK table


30° 360° | CRI ≥ 90 | 220-240 V | DIM 10-100% | MOVE sensor | USB connector | X-PERT | presence

OPAL | DIRECT CRI ≥ 90, touch DIM / stand alone sensor

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.1 W	3000 K	950 lm	94 lm/W	059-281107 O
	4000 K	1010 lm	100 lm/W	059-281117 O



Mounting accessories (required)



BASE PLATE

Ø·H (mm)	ORDER CODE
220·13	059-289111



TABLE CLAMP height 77-88 mm

Ø (mm)	ORDER CODE
75	059-289211

for hole ø68 mm, 10–30 mm range

Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8