



## TASK

wall


<sup>EN</sup> Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; suitable for wall mounting; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special PCBs with asymmetrical light distribution; for optimum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering

<sup>IT</sup> Corpo illuminante rettangolare in alluminio con bordi arrotondati; forma ultrapiatta (solo 15 mm); verniciatura a polvere; montaggio a parete; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; direzionamento della luce con materiale del riflettore altamente riflettente; percentuale indiretta con piastre dedicate a distribuzione asimmetrica della luce; per un'illuminazione ottimale del soffitto; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 90 / 3 SDCM (initial MacAdam)  
 fino a ↓ 1,970 lm / ↑ 3,760 lm  
 fino a 127 lm/W  
 L90 / 50000 h  
 DALI-2  
 Microprismatic  
 IP20

### Types



### Colore



### Distribuzione della luce



asymmetrical ceiling illumination




### TASK wall




MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
45.0 W	3000 K	↓1850/↑3530 lm	120 lm/W	0 5 9 - 2 0 3 2 0 3 <input checked="" type="checkbox"/> Z
	4000 K	↓1970/↑3760 lm	127 lm/W	0 5 9 - 2 0 3 2 1 3 <input checked="" type="checkbox"/> Z



### Planning Information



#### TASK wall

46W, 4000K, direct/indirect power

#### ROOM VALUES


Room dimensions	5.4 × 4.0 × 2.8m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Mounting height	2.25m

#### CALCULATION SURFACE

Surface dimensions	Floor
Surface height	0m

#### GLARE EVALUATION

Table Classification	X=4H   Y=8H   S=0.25H
UGR transversal	≤ 19
UGR axial	≤ 19



### Order options

COLOUR	
pure white RAL 9010	7 <input checked="" type="checkbox"/>
jet black RAL 9005	8