



SONO IP54

surface


^{EN} Round luminaire housing in die-cast aluminium; surface powder coated; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

^{IT} Corpo illuminante rotondo in alluminio pressofuso; verniciatura a polvere; per montaggio a parete o soffitto; diffusore satinato in PMMA a illuminazione assolutamente omogenea; stessa luminosità nei modelli di tutte le dimensioni; LED ad efficienza energetica con elevata resa cromatica; apparecchio con 2 ingressi cavi e morsetto per cablaggio passante

Quickinfo

3000 K, 4000 K
 CRI \geq 80 / 3 SDCM (initial MacAdam)
 fino a 147 lm/W
 L90 / 50000 h
 DALI-2, non DIM
 Opal
 IP54, IK07

Types



Colore



Distribuzione della luce




DiiA® standards
 251, 252, 253



easy mounting
 by click-
 mechanism



dust & insect
 protection (IP
 54)



tunable white
 2700 – 6500 K
 (optional)




SONO 260 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|-----------|----------|-------------------------|
| 7.0 W | 3000 K | 950 lm | 136 lm/W | 8 7 1 - 9 1 2 6 5 ◆ 7 0 |
| | 4000 K | 1010 lm | 144 lm/W | 8 7 1 - 9 1 2 6 6 ◆ 7 0 |




SONO 350 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|-----------|----------|-------------------------|
| 15.9 W | 3000 K | 2090 lm | 131 lm/W | 8 7 1 - 9 1 3 6 5 ◆ 7 0 |
| | 4000 K | 2210 lm | 139 lm/W | 8 7 1 - 9 1 3 6 6 ◆ 7 0 |




SONO 450 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|-----------|----------|-------------------------|
| 23.2 W | 3000 K | 3060 lm | 132 lm/W | 8 7 1 - 9 1 4 6 5 ◆ 7 0 |
| | 4000 K | 3240 lm | 140 lm/W | 8 7 1 - 9 1 4 6 6 ◆ 7 0 |



Order options

| CONTROL | | COLOUR | |
|---------|---|------------|----------|
| non DIM | 1 | pure white | RAL 9010 |
| DALI-2 | 3 | | |




SONO 600 ip54 surface



OPAL | DIRECT pure white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------------|-----------|----------|---|
| 42.0 W | 3000 K | 5830 lm | 139 lm/W | 8 7 1 - 9 1 5 6 5 ◆ 7 0 |
| | 4000 K | 6170 lm | 147 lm/W | 8 7 1 - 9 1 5 6 6 ◆ 7 0 |



Mounting tools accessories (optional)

DISMOUNTING TOOL

| TYPE | ORDER CODE |
|------------|-------------------|
| vacuum cup | 0 8 6 - 3 0 0 0 0 |

Order options

| CONTROL | | COLOUR | |
|---------|---|------------|----------|
| non DIM | 1 | pure white | RAL 9010 |
| DALI-2 | 3 | | |