
Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 19, UGR ≤ 25
fino a 140 lm/W
L85 / 50000 h
DALI-2
Asymmetric Wallwasher, Jut-Out, Microprismatic, Opal
IP40 / back IP20 / classe isolamento 2 / 220-240 V
613 mm, 1.221 mm, 1.830 mm, 2.438 mm,

Types



Colours

Distribuzione della luce

LENO


trimless system

EN Low profile recessed channel; suitable for trimless installation in 12.5 mm plasterboard ceilings; suitable for wall or ceiling mounting; designed for continuous lighting systems; surface powder coated; special edge design with grooves for better adhesion of filler; easy mounting without need to cut the substructure; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; optional with asymmetric light distribution; energy-efficient LEDs with very good colour rendering; incl. external converter for ceiling insertion

IT Apparecchio da incasso ultrapiatto; per incasso a scomparsa in soffitto di cartongesso di 12,5 mm; per montaggio a parete o soffitto; per sistemi di file continue; verniciatura a polvere; bordatura speciale scanalata per una migliore aderenza dello stucco; montaggio semplice senza taglio della struttura sottostante; inserto luce anti-caduta in profilo di allumino estruso, fissaggio nel canale con magnete senza bisogno di utensili; luce convogliata lateralmente e direzionata in basso con sistema LGP-Body (Light Guiding Prism) e riflettore ad alta efficienza; diffusore satinato (a filo o sporgente) o con struttura a microprismi a illuminazione omogenea in PMMA; in opzione con distribuzione asimmetrica della luce; LED ad efficienza energetica con elevata resa cromatica; incl. converter esterno da inserire nel soffitto



DiiA® standards
251, 252, 253




microprismatic
UGR ≤ 19



quick
installation

LENO trimless system






INSTALLATION CHANNEL trimless

L·W·H (mm)	ORDER CODE
613·92·13	051-8900067
1221·92·13	051-8900127
1830·92·13	051-8900187
2438·92·13	051-8900247

order installation channel, light inset + mounting accessories separately



LIGHT INSET

CRI ≥ 80 · UGR ≤ 19 · 220-240 V · DALI 1 ADDR. · IP20 IP40 · X-PERT

MICROPRISMATIC traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	613 mm	1230 lm	124 lm/W	051-80125:37G
19.1 W	1221 mm	2450 lm	128 lm/W	051-80145:37G
28.6 W	1830 mm	3680 lm	129 lm/W	051-80165:37G
37.0 W	2438 mm	4910 lm	133 lm/W	051-80185:37G

OPAL traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	613 mm	1300 lm	131 lm/W	051-80125:37H
19.1 W	1221 mm	2590 lm	136 lm/W	051-80145:37H
28.6 W	1830 mm	3890 lm	136 lm/W	051-80165:37H
37.0 W	2438 mm	5190 lm	140 lm/W	051-80185:37H

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour temperature 4000 K.

OPAL JUT-OUT traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	613 mm	1240 lm	125 lm/W	051-80125:37J
19.1 W	1221 mm	2490 lm	130 lm/W	051-80145:37J
28.6 W	1830 mm	3730 lm	130 lm/W	051-80165:37J
37.0 W	2438 mm	4970 lm	134 lm/W	051-80185:37J

ASYMMETRIC traffic white, CRI ≥ 80, DALI-2


SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
15.6 W	613 mm	1660 lm	106 lm/W	051-80125:37A
30.0 W	1221 mm	3320 lm	111 lm/W	051-80145:37A
46.0 W	1830 mm	4990 lm	108 lm/W	051-80165:37A
60.0 W	2438 mm	6650 lm	111 lm/W	051-80185:37A


Order options

COLOUR TEMPERATURE	::
3000 K	5
4000 K	6

COLOUR	
traffic white	RAL 9016

Planning Information





LENO trimless, microprismatic, 19.1 W, 4000 K

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 | 0.5 | 0.2
Maintenance factor	0.8

CALCULATION SURFACE ·····

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Mounting accessories (optional)



END CAPS trimless 1 pair

W·H (mm)	ORDER CODE
92·13	051-8990217



LINEAR CONNECTOR recessed

TYPE	L·W (mm)	ORDER CODE
1 pair	48·19	051-8990110
10 pairs	48·19	051-8990110 · 10

Mounting tools accessories (optional)

DISMOUNTING TOOL


TYPE	ORDER CODE
vacuum cup	086-30000

Vaucluse House, Australia

Australia

Lighting Design
EST Lighting

Fotografo
Katherine Lu




Prodotti utilizzati



LENO trimless system

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com










M9

