

Quickinfo

2700 K, 3000 K, 4000 K, colour
warm dimming 1800 - 2700 K
CRI ≥ 90 , CRI ≥ 95 / 2 SDCM
(initial MacAdam), 3 SDCM (initial
MacAdam), 4 SDCM (initial
MacAdam)
UGR ≤ 10 , UGR ≤ 19
fino a 103 lm/W
L80 / 50000 h, L85 / 50000 h,
L90 / 50000 h, L95 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours



Set di montaggio



Distribuzione della luce



SASSO PRO 80 adjustable offset round

recessed

^{EN} Round recessed spotlight in die-cast aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; surface powder coated; light inset rotatable and tiltable; offset lighting level; optical attachments available as accessories; with optional high-quality lens system with precise radiation characteristic; and high-quality reflector with spherical facet effect design, precise radiation characteristic with two different beam angles; installed and exchanged without tools; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

^{IT} Faretto da incasso rotondo in alluminio pressofuso; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura a polvere; inserto luce girevole e orientabile; superficie di emissione arretrata; unità ottiche disponibili come accessori; a scelta con ottica lenticolare di precisione; oppure con riflettore a sfaccettature sferiche, curva fotometrica precisa con due diversi angoli di emissione; montaggio e smontaggio senza utensili; con tecnologia COB (Chip on Board) o LED high power per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica



DiiA® standards
251, 252, 253



360° rotatable,
35° tiltable



Colour Warm
Dimming 1800 –
2700 K



SASSO PRO 80 adjustable



SUPER SPOT 8°, CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W	2700 K	388 lm	55 lm/W	0 4 8 - 2 3 1 0 4 1 ☒ V
	3000 K	379 lm	54 lm/W	0 4 8 - 2 3 1 0 5 1 ☒ V
	4000 K	408 lm	58 lm/W	0 4 8 - 2 3 1 0 6 1 ☒ V


MEDIUM 26°,

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.5 W	CWD, CRI ≥ 95	377 lm	58 lm/W	0 4 8 - 2 3 1 0 E 3 ☒ M
7.5 W	2700 K, CRI ≥ 90	721 lm	96 lm/W	0 4 8 - 2 3 1 0 4 1 ☒ M
	3000 K, CRI ≥ 90	757 lm	101 lm/W	0 4 8 - 2 3 1 0 5 1 ☒ M
	4000 K, CRI ≥ 90	765 lm	102 lm/W	0 4 8 - 2 3 1 0 6 1 ☒ M
12.2 W	2700 K, CRI ≥ 90	1010 lm	83 lm/W	0 4 8 - 2 3 1 2 4 ☒ M
	3000 K, CRI ≥ 90	1050 lm	86 lm/W	0 4 8 - 2 3 1 2 5 ☒ M
	4000 K, CRI ≥ 90	1120 lm	92 lm/W	0 4 8 - 2 3 1 2 6 ☒ M

FLOOD 37°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.5 W	2700 K	728 lm	97 lm/W	0 4 8 - 2 3 1 0 4 1 ☒ F
	3000 K	765 lm	102 lm/W	0 4 8 - 2 3 1 0 5 1 ☒ F
	4000 K	773 lm	103 lm/W	0 4 8 - 2 3 1 0 6 1 ☒ F
12.2 W	2700 K	1020 lm	84 lm/W	0 4 8 - 2 3 1 2 4 ☒ F
	3000 K	1060 lm	87 lm/W	0 4 8 - 2 3 1 2 5 ☒ F
	4000 K	1130 lm	93 lm/W	0 4 8 - 2 3 1 2 6 ☒ F

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings, 12.5/15/25 mm

L-W-H (mm)	ORDER CODE
124-92-33	0 5 2 - 1 9 3 1 3 2 ☒




MOUNTING SET with trim for intermediate ceilings, 5-25 mm

Ø-H (mm)	ORDER CODE
98-43	0 5 2 - 1 9 3 2 3 2 ☒

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8



Mounting accessories (optional)

PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)

240-400-130

ORDER CODE

0 5 2 - 1 9 1 4 3 2 0

order mounting set separately

Optical accessories (optional)



HONEYCOMB LOUVER

Ø·H (mm)

54·11

ORDER CODE

0 4 8 - 2 0 9 1 3 1 ☒

LINEAR PRISMATIC LENS

Ø·H (mm)

54·11

ORDER CODE

0 4 8 - 2 0 9 2 3 1 ☒



SNOOT

Ø·H (mm)

54·25

ORDER CODE

0 4 8 - 2 0 9 1 1 1 ☒



SNOOT WITH HONEYCOMB LOUVER

Ø·H (mm)

54·25

ORDER CODE

0 4 8 - 2 0 9 1 2 1 ☒

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8