




Quickinfo

2700 K, 3000 K, 4000 K, colour warm dimming 2000 - 3000 K, tunable white 1800 - 3000 K, tunable white 2700 - 6500 K
CRI ≥ 90, CRI ≥ 92, CRI ≥ 95 / 3 SDCM (initial MacAdam), 4 SDCM (initial MacAdam)
UGR ≤ 19
fino a 105 lm/W
L70 / 50000 h, L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours

Set di montaggio


Distribuzione della luce

SASSO PRO 100 adjustable offset round

recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; surface powder coated; light inset rotatable and tiltable; offset lighting level; optical attachments available as accessories; high-quality reflector with spherical facet effect design, precise radiation characteristics with different beam angles; installed and exchanged without tools; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

IT Faretto da incasso rotondo in alluminio pressofuso; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura a polvere; inserto luce girevole e orientabile; superficie di emissione arretrata; unità ottiche disponibili come accessori; riflettore a sfaccettature sferiche, curva fotometrica precisa con diversi angoli di emissione; montaggio e smontaggio senza utensili; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica



360° rotatable, 35° tiltable




Colour Warm Dimming 2000 – 3000 K



tunable white 1800 – 3000 K or 2700 – 6500 K





SASSO PRO 100 adjustable

35° 360° | CRI ≥ 95 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SPOT 17°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	0 4 8 - 2 4 1 0 4 ◆ ◪ S
	3000 K	1410 lm	96 lm/W	0 4 8 - 2 4 1 0 5 ◆ ◪ S
	4000 K	1490 lm	101 lm/W	0 4 8 - 2 4 1 0 6 ◆ ◪ S
27.0 W	2700 K	2170 lm	80 lm/W	0 4 8 - 2 4 1 2 4 ◆ ◪ S
	3000 K	2270 lm	84 lm/W	0 4 8 - 2 4 1 2 5 ◆ ◪ S
	4000 K	2400 lm	89 lm/W	0 4 8 - 2 4 1 2 6 ◆ ◪ S

MEDIUM 24°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	0 4 8 - 2 4 1 0 4 ◆ ◪ M
	3000 K	1410 lm	96 lm/W	0 4 8 - 2 4 1 0 5 ◆ ◪ M
	4000 K	1490 lm	101 lm/W	0 4 8 - 2 4 1 0 6 ◆ ◪ M
27.0 W	2700 K	2170 lm	80 lm/W	0 4 8 - 2 4 1 2 4 ◆ ◪ M
	3000 K	2270 lm	84 lm/W	0 4 8 - 2 4 1 2 5 ◆ ◪ M
	4000 K	2400 lm	89 lm/W	0 4 8 - 2 4 1 2 6 ◆ ◪ M

FLOOD 36°-38°,


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K, CRI ≥ 90	1360 lm	93 lm/W	0 4 8 - 2 4 1 0 4 ◆ ◪ F
	3000 K, CRI ≥ 90	1420 lm	97 lm/W	0 4 8 - 2 4 1 0 5 ◆ ◪ F
	4000 K, CRI ≥ 90	1500 lm	102 lm/W	0 4 8 - 2 4 1 0 6 ◆ ◪ F
14.9 W	CWD, CRI ≥ 95	853 lm	57 lm/W	0 4 8 - 2 4 1 1 E 3 ◪ F
27.0 W	2700 K, CRI ≥ 90	2190 lm	81 lm/W	0 4 8 - 2 4 1 2 4 ◆ ◪ F
	3000 K, CRI ≥ 90	2280 lm	84 lm/W	0 4 8 - 2 4 1 2 5 ◆ ◪ F
	4000 K, CRI ≥ 90	2420 lm	90 lm/W	0 4 8 - 2 4 1 2 6 ◆ ◪ F

WIDE FLOOD 57°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1280 lm	87 lm/W	0 4 8 - 2 4 1 0 4 ◆ ◪ W
	3000 K	1340 lm	91 lm/W	0 4 8 - 2 4 1 0 5 ◆ ◪ W
	4000 K	1420 lm	97 lm/W	0 4 8 - 2 4 1 0 6 ◆ ◪ W
27.0 W	2700 K	2070 lm	77 lm/W	0 4 8 - 2 4 1 2 4 ◆ ◪ W
	3000 K	2160 lm	80 lm/W	0 4 8 - 2 4 1 2 5 ◆ ◪ W
	4000 K	2280 lm	84 lm/W	0 4 8 - 2 4 1 2 6 ◆ ◪ W

Order options

CONTROL ◆		COLOUR ◪	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8




SASSO PRO 100 adjustable high output

35° 360° | CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT


MEDIUM 26°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.0 W	3000 K	2790 lm	103 lm/W	0 4 8 - 2 4 1 3 5 ◆ ◪ M
	4000 K	2820 lm	104 lm/W	0 4 8 - 2 4 1 3 6 ◆ ◪ M



FLOOD 39°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.0 W	3000 K	2810 lm	104 lm/W	0 4 8 - 2 4 1 3 5 ◆ ◪ F
	4000 K	2840 lm	105 lm/W	0 4 8 - 2 4 1 3 6 ◆ ◪ F




SASSO PRO 100 adjustable (tunable white)


35° 360° | TUNABLE WHITE | CRI ≥ 92 | 220-240 V | 2 ADDR. | X-PERT | X-PERT

FLOOD 38°, CRI ≥ 92, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
21.0 W	tunable w., 1800 - 3000 K	1450 lm	69 lm/W	0 4 8 - 2 4 1 2 L 3 ◪ F
28.2 W	tunable w., 2700 - 6500 K	2180 lm	77 lm/W	0 4 8 - 2 4 1 2 D 3 ◪ F



Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings, 12.5/15/25 mm

L·W·H (mm)	ORDER CODE
149·113·33	0 5 2 - 1 9 3 1 4 4 ◪




MOUNTING SET with trim for intermediate ceilings, 5-25 mm

Ø·H (mm)	ORDER CODE
112·43	0 5 2 - 1 9 3 2 4 4 ◪

Order options

CONTROL ◆		COLOUR ◪	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Mounting accessories (optional)



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
240·400·130	052-191442 0

order mounting set separately

Optical accessories (optional)

HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
74·11	048-219131

LINEAR PRISMATIC LENS

Ø·H (mm)	ORDER CODE
74·11	048-219231



SNOOT

Ø·H (mm)	ORDER CODE
74·25	048-219111



SNOOT WITH HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
74·25	048-219121

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

Health Resort Lanserhof Sylt

Germania

Architetto
ingenhoven architects

Lighting Design
Tropp Lighting Design

Fotografo
HGEsch



Prodotti utilizzati



SASSO PRO 100 adjustable offset round recessed

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com





